

Package ‘varunayan’

October 29, 2026

Type Package

Title Download and Process 'ERA5', IMD, 'HadEX3' and 'CRU TS' Data

Version 0.4.0

Description Download climate data for a bounding box, polygon or point and return tidy tables. Sources are the 'ERA5' reanalysis (Hersbach et al. (2020) <[doi:10.1002/qj.3803](https://doi.org/10.1002/qj.3803)>) from the 'Copernicus' Climate Data Store <<https://cds.climate.copernicus.eu/>>, India Meteorological Department (IMD) gridded rainfall and temperature (Pai et al. (2014) <[doi:10.54302/mausam.v65i1.851](https://doi.org/10.54302/mausam.v65i1.851)>), 'HadEX3' climate extremes (Dunn et al. (2020) <[doi:10.1029/2019JD032263](https://doi.org/10.1029/2019JD032263)>) and 'CRU TS' (Harris et al. (2020) <[doi:10.1038/s41597-020-0453-3](https://doi.org/10.1038/s41597-020-0453-3)>). Computes heat stress indices, including wet-bulb globe temperature (Liljegren et al. (2008) <[doi:10.1080/15459620802310770](https://doi.org/10.1080/15459620802310770)>) and the Universal Thermal Climate Index (Bröde et al. (2012) <[doi:10.1007/s00484-011-0454-1](https://doi.org/10.1007/s00484-011-0454-1)>), and heatwave indicators, including the Excess Heat Factor (Nairn and Fawcett (2015) <[doi:10.3390/ijerph120100227](https://doi.org/10.3390/ijerph120100227)>).

License MIT + file LICENSE

URL <https://varunayan.saketlab.org/R/>,
<https://github.com/saketlab/varunayan>

BugReports <https://github.com/saketlab/varunayan/issues>

Depends R (>= 4.1.0)

Imports data.table, digest, dplyr, ecmwfr (>= 2.0.0), httr, jsonlite, lubridate, magrittr, ncdf4, rlang, sf, stars, stats, terra, tools, utils, parallel

Suggests ggplot2, ggpubr, gridExtra, knitr, maps, ncmeta, patchwork, R.utils, rmarkdown, scales, testthat (>= 3.1.7), tidyr, units, withr (>= 2.5.0)

VignetteBuilder knitr

Config/roxygen2/version 8.1.1

Config/testthat/edition 3

Copyright See file inst/COPYRIGHTS

Encoding UTF-8

Language en-US

NeedsCompilation no

Author Saket Choudhary [aut, cre, cph] (ORCID:
<https://orcid.org/0000-0001-5202-7633>),
 Darakhshan Nehal [aut],
 James C. Liljegren [ctb] (Author of the original WBGT C code),
 UChicago Argonne, LLC [cph] (Copyright holder of the original WBGT C
 code)

Maintainer Saket Choudhary <saketc@iitb.ac.in>

Repository CRAN

Date/Publication 2026-10-29 19:30:02 UTC

Contents

aggregate_by_frequency	5
aggregate_imd_by_frequency	6
aggregate_to_polygons	6
anomaly	8
cache_stats	8
calc_heat_indices	9
categorize_variables	9
CheckSystemReadiness	10
check_grid_coverage	10
cleanup_temp_files	11
ClearCache	12
clear_timings	12
combine_netcdf_files	13
compare	13
compare_grids	14
convert_to_geojson	15
create_geojson_from_bbox	15
create_temporal_chunks	16
create_temp_geojson_file	16
cross_correlation	17
CRUTSBbox	18
CRUTSGeojson	19
DescribeVariables	20
dewpoint_from_relative_humidity	21
download_era5_pressure	21
download_era5_single	22
download_imd_rainfall	23
download_imd_temperature	24
ensure_output_dir	25
ERA5ifyBbox	25
ERA5ifyPoint	27

excess_heat_factor	29
exclude_cols	30
exposure_indicators	30
extract_point_data	32
filter_dataframe_by_geojson	33
filter_imd_by_bbox	33
filter_imd_by_geojson	34
filter_netcdf_by_bbox	35
filter_netcdf_by_geojson	35
format_date_range	36
format_pressure_levels	36
GetAvailablePressureLevels	37
GetCacheDir	37
GetERA5CountryTemperature	38
GetERA5DailyClimate	39
GetERA5DailyHeatIndexData	41
GetERA5DailyHumidity	43
GetERA5DailyTemperature	44
GetERA5DailyWetBulb	46
GetERA5DailyWind	47
GetERA5MonthlyHeatIndexData	49
GetPackageInfo	51
get_available_datasets	51
get_bbox_from_sf	52
get_cds_credentials	52
get_imd_grid_specs	53
get_pressure_level_variables	53
get_pressure_level_variable_names	54
get_single_level_variables	54
get_single_level_variable_names	54
get_time_values	55
get_timings	55
HadEX3Bbox	56
HadEX3Geojson	57
heatwave_days	58
heat_index	60
heat_index_from_dewpoint	60
heat_index_risk_category	61
humidex	61
IMDExposureBbox	62
IMDRainfallBbox	63
IMDRainfallGeojson	64
IMDRainfallPoint	66
IMDStations	67
IMDTemperatureBbox	68
IMDTemperatureGeojson	69
imd_temperature_by_region	70
imd_terrain	71

india_elevation	73
is_max_var	73
is_min_var	74
is_rate_var	75
is_sum_var	75
is_valid_geojson	76
ListAvailableVariables	76
ListCRUTSVVariables	77
ListHadEX3Indices	77
list_cache	78
list_imd_datasets	78
load_india_boundaries	79
max_vars	79
mean_radiant_temperature	80
min_vars	80
ndbi	81
ndvi	82
parse_date_flexible	82
peak_month	83
plot_bars	84
plot_ccf	85
plot_dual_axis	85
plot_heatmap	86
plot_map	87
plot_scatter	88
plot_series	89
PopulateSampleCache	90
print_timing_summary	90
process_imd_files	91
process_netcdf_to_dataframe	92
rate_vars	92
read_cdsapirc	93
read_imd_rainfall	93
read_imd_temperature	94
regrid	95
relative_humidity_from_dewpoint	96
SearchVariable	96
seasonal_cycle	97
seasonal_stat	98
SetupCdsCredentials	99
ShowCacheInfo	99
spatial_mean	100
sum_vars	101
time_operation	101
utci	102
utci_category	102
utci_sparse	103
validate_bbox	104

<i>aggregate_by_frequency</i>	5
validate_coordinates	104
validate_era5_variables	105
vapor_pressure_from_dewpoint	105
varunayan-aliases	106
visualize_grid_overlap	107
warm_nights	109
wbgt	110
wbgt_from_dewpoint	111
wbgt_liljegren	111
wbgt_risk_category	113
wbgt_shade	114
wbgt_simple	114
wet_bulb_from_dewpoint	115
wet_bulb_temperature	116
Index	117

aggregate_by_frequency
<i>Aggregate data by temporal frequency</i>

Description

Aggregate data by temporal frequency

Usage

aggregate_by_frequency(data, frequency, verbose = FALSE)

Arguments

- | | |
|-----------|---|
| data | data.frame with datetime column |
| frequency | Character string: "daily", "monthly", "yearly" |
| verbose | Logical. If TRUE, the function prints progress messages |

Value

data.frame with temporally aggregated data

aggregate_imd_by_frequency
<i>Aggregate IMD data by temporal frequency</i>

Description

Aggregate IMD data by temporal frequency

Usage

```
aggregate_imd_by_frequency(data, frequency = "daily")
```

Arguments

data	data.frame with IMD data
frequency	Character string: "daily", "monthly", "yearly"

Value

A data.frame with columns date (first day of each month or year), latitude, longitude and the value column, summed for rainfall and averaged for temperature. Returned unchanged when frequency = "daily".

Examples

```
imd <- data.frame(  
  date = rep(as.Date("2023-01-01") + 0:59, each = 2),  
  latitude = 20.5, longitude = c(73.5, 79.5), rainfall = 1  
)  
aggregate_imd_by_frequency(imd, "monthly")
```

aggregate_to_polygons	<i>Aggregate gridded data to polygon regions</i>
-----------------------	--

Description

Assigns each grid cell to a polygon, then aggregates the values of the cells in each polygon. The spatial match uses only the distinct cells. Thus, a daily series with many dates does not make the match slower.

Usage

```

aggregate_to_polygons(
  data,
  polygons,
  value_col,
  method = c("nearest_centroid", "point_in_polygon"),
  polygon_id_cols = NULL,
  agg_fun = function(x) mean(x, na.rm = TRUE),
  by = NULL,
  fill_empty = FALSE
)

```

Arguments

<code>data</code>	Data frame with longitude, latitude, and value columns
<code>polygons</code>	sf object with polygon geometries (CRS 4326)
<code>value_col</code>	Name of the column to aggregate, or a character vector of names. Give names to set the result columns, for example <code>c(tmean = "temp_c")</code> . A column without a name keeps its name.
<code>method</code>	Aggregation method: "nearest_centroid" (each polygon gets the cell nearest to a point on its surface) or "point_in_polygon" (each polygon gets the cells in it)
<code>polygon_id_cols</code>	Character vector of column names to use as polygon identifiers. The default is all the columns of polygons except the geometry.
<code>agg_fun</code>	Aggregation function. It gets the values of one group, which can include NA. The default is the mean without the NA values.
<code>by</code>	Optional character vector of more group columns in data, for example "date". The result then has one row for each polygon and each value of by.
<code>fill_empty</code>	For "point_in_polygon": if TRUE, a polygon with no cell in it (smaller than a cell) gets the cell nearest to a point on its surface.

Value

Data frame with the polygon identifiers, the by columns and the aggregated values. It has one row for each polygon and each value of by. A polygon with no cell has NA.

Examples

```

grid <- expand.grid(longitude = seq(72.5, 77.5, by = 1), latitude = seq(18.5, 21.5, by = 1))
grid$temperature <- seq_len(nrow(grid))
cells <- sf::st_make_grid(sf::st_as_sfc(sf::st_bbox(
  c(xmin = 72, ymin = 18, xmax = 78, ymax = 22),
  crs = 4326
)), n = c(2, 1))
polys <- sf::st_sf(region = c("west", "east"), geometry = cells)
aggregate_to_polygons(grid, polys, value_col = "temperature")

```

anomaly	<i>Departure from the mean over a baseline period</i>
---------	---

Description

Departure from the mean over a baseline period

Usage

```
anomaly(data, value, baseline = NULL, year_col = "year")
```

Arguments

data	Data frame with value (and year_col if a baseline is set)
value	Name of the column to use
baseline	Optional c(first_year, last_year). The default uses all rows.
year_col	Name of the year column for the baseline

Value

Numeric vector of anomalies, one for each row of data

Examples

```
df <- data.frame(year = 2001:2005, t2m = c(25, 26, 25.5, 27, 26.5))
anomaly(df, "t2m")
```

cache_stats	<i>Get cache statistics</i>
-------------	-----------------------------

Description

Get cache statistics

Usage

```
cache_stats()
```

Value

A list with elements exists (logical), n_files and total_size_mb.

Examples

```
cache_stats()
```

calc_heat_indices	<i>Calculate all heat stress indices</i>
-------------------	--

Description

This function calculates all heat stress indices from temperature and dewpoint.

Usage

```
calc_heat_indices(temp_c, dewpoint_c)
```

Arguments

temp_c	Air temperature in Celsius
dewpoint_c	Dewpoint temperature in Celsius

Value

Data frame with columns: temp_c, dewpoint_c, rh, wet_bulb, heat_index, wbgt, humidex

Examples

```
calc_heat_indices(35, 25)
calc_heat_indices(c(30, 35, 40), c(20, 25, 28))
```

categorize_variables	<i>Sort variables by aggregation method</i>
----------------------	---

Description

Sort variables by aggregation method

Usage

```
categorize_variables(var_names)
```

Arguments

var_names	Character vector of variable names
-----------	------------------------------------

Value

Named list of the variables, sorted by aggregation method

Examples

```
categorize_variables(c("2m_temperature", "total_precipitation"))
```

CheckSystemReadiness	<i>Make sure that the system is ready for varunayan operations</i>
----------------------	--

Description

Make sure that the system is ready for varunayan operations

Usage

```
CheckSystemReadiness(...)
check_system_readiness(verbose = TRUE)
```

Arguments

...	Arguments for the main function (for use by aliases).
verbose	If TRUE, print detailed information

Value

Invisibly, TRUE if all required packages, network access and CDS credentials are available, FALSE otherwise.

Examples

```
check_system_readiness()
```

check_grid_coverage	<i>Calculate the grid coverage statistics for polygons</i>
---------------------	--

Description

Calculate the grid coverage statistics for polygons

Usage

```
check_grid_coverage(grid_data, polygons, polygon_id_cols = NULL)
```

Arguments

grid_data	Data frame with longitude and latitude columns
polygons	sf object with polygon geometries
polygon_id_cols	Column names that identify the polygons

Value

A list with elements `total_polygons`, `total_grid_points`, `polygons_with_points`, `polygons_without_points`, `coverage_percent`, `points_per_polygon` (a data.frame of polygon identifiers and `n_points`) and `summary` (a one-line character description).

Examples

```
grid <- expand.grid(longitude = seq(72.5, 77.5, by = 1), latitude = seq(18.5, 21.5, by = 1))
grid$temperature <- seq_len(nrow(grid))
cells <- sf::st_make_grid(sf::st_as_sfc(sf::st_bbox(
  c(xmin = 72, ymin = 18, xmax = 78, ymax = 22),
  crs = 4326
)), n = c(2, 1))
polys <- sf::st_sf(region = c("west", "east"), geometry = cells)
check_grid_coverage(grid, polys)
```

cleanup_temp_files	<i>Delete temporary files that match a pattern</i>
--------------------	--

Description

Delete temporary files that match a pattern

Usage

```
cleanup_temp_files(pattern = "varunayan_.*", directory = tempdir())
```

Arguments

pattern	Regular expression pattern to match files
directory	Directory for the search (default: <code>tempdir()</code>)

Value

Number of files removed

ClearCache	<i>Clear cache</i>
------------	--------------------

Description

Clear cache

Usage

```
ClearCache(...)
```

```
clear_cache(source = NULL, older_than = NULL, confirm = TRUE)
```

Arguments

...	Arguments for the main function (for use by aliases).
source	Clear only "era5", "imd", "cru_ts", "hadex3", or NULL for all
older_than	Remove files that are older than this number of days (NULL = all)
confirm	Ask for confirmation (default: TRUE)

Value

Invisibly, the number of files deleted.

Examples

```
# Remove cached ERA5 files older than 30 days
clear_cache(source = "era5", older_than = 30)
```

clear_timings	<i>Clear all time data</i>
---------------	----------------------------

Description

Clear all time data

Usage

```
clear_timings()
```

Value

NULL, invisibly. Called for its side effect.

Examples

```
clear_timings()
```

combine_netcdf_files	<i>Combine NetCDF files into one data.frame</i>
----------------------	---

Description

Combine NetCDF files into one data.frame

Usage

```
combine_netcdf_files(netcdf_files, verbose = FALSE)
```

Arguments

netcdf_files	Character vector of NetCDF file paths
verbose	Logical. If TRUE, the function prints progress messages

Value

data.frame with combined data from all files

compare	<i>Agreement statistics between two columns</i>
---------	---

Description

Rows where x or y is missing are removed first.

Usage

```
compare(data, x, y, by = NULL)
```

Arguments

data	Data frame with the two columns, for example after a merge
x	First column (for example the reference dataset)
y	Second column
by	Optional group columns, for example "state_name"

Value

Data frame with the by columns, n, r (Pearson), bias (mean of y - x) and rmse

Examples

```
df <- data.frame(imd = c(1, 2, 3, 4), era5 = c(1.1, 2.3, 2.9, 4.2))
compare(df, "imd", "era5")
```

compare_grids	<i>Compare two or more grids</i>
---------------	----------------------------------

Description

Compare two or more grids

Usage

```
compare_grids(
  ...,
  polygons = NULL,
  colors = NULL,
  shapes = NULL,
  point_size = 1,
  polygon_color = "#2C3E50",
  title = "Grid Comparison"
)
```

Arguments

...	Named data frames with longitude and latitude columns
polygons	Optional sf object to show polygon boundaries
colors	Named vector of colors for each grid
shapes	Named vector of point shapes for each grid
point_size	Size of grid points
polygon_color	Color for polygon boundaries
title	Plot title

Value

ggplot object

Examples

```
grid <- expand.grid(longitude = seq(72.5, 77.5, by = 1), latitude = seq(18.5, 21.5, by = 1))
grid$temperature <- seq_len(nrow(grid))
cells <- sf::st_make_grid(sf::st_as_sfc(sf::st_bbox(
  c(xmin = 72, ymin = 18, xmax = 78, ymax = 22),
  crs = 4326
)), n = c(2, 1))
polys <- sf::st_sf(region = c("west", "east"), geometry = cells)
coarse <- grid[grid$longitude < 75, ]
compare_grids(fine = grid, coarse = coarse, polygons = polys)
```

convert_to_geojson	<i>Convert data to GeoJSON format</i>
--------------------	---------------------------------------

Description

Convert data to GeoJSON format

Usage

```
convert_to_geojson(data)
```

Arguments

data	Data to convert (must be data.frame with lon/lat columns)
------	---

Value

Data in GeoJSON format

create_geojson_from_bbox	<i>Create GeoJSON from bounding box coordinates</i>
--------------------------	---

Description

Create GeoJSON from bounding box coordinates

Usage

```
create_geojson_from_bbox(north, south, east, west)
```

Arguments

north	Northern latitude
south	Southern latitude
east	Eastern longitude
west	Western longitude

Value

GeoJSON object that shows the bounding box

```
create_temporal_chunks
```

Divide large date ranges into temporal chunks

Description

The default chunk size is `compute_optimal_chunk_size(frequency)`. This size changes with the CDS field limit (hourly: 24 fields/day, daily: 1/day, monthly: 12/year). Thus, each chunk fills one CDS job.

Usage

```
create_temporal_chunks(
  start_date,
  end_date,
  frequency,
  n_variables = 1L,
  max_days_per_chunk = NA
)
```

Arguments

<code>start_date</code>	Start date
<code>end_date</code>	End date
<code>frequency</code>	Temporal frequency ("hourly", "daily", "monthly")
<code>n_variables</code>	Number of variables in the request (fields = vars x steps)
<code>max_days_per_chunk</code>	Maximum days per chunk. If NA (default), the function calculates the value from frequency with <code>compute_optimal_chunk_size</code> .

Value

List of date pairs, with one pair for each chunk

```
create_temp_geojson_file
```

Create temporary GeoJSON file

Description

Create temporary GeoJSON file

Usage

```
create_temp_geojson_file(geojson_data, request_id)
```

Arguments

geojson_data GeoJSON data to write
request_id Request identifier for a unique filename

Value

Path to temporary GeoJSON file

cross_correlation	<i>Cross-correlation of two series</i>
-------------------	--

Description

This is `stats::ccf()` as a data frame. r at lag k estimates $\text{cor}(x[t + k], y[t])$. A peak at a negative lag means that x changes before y .

Usage

```
cross_correlation(x, y, max_lag = 12)
```

Arguments

x First series
 y Second series, same length as x
 max_lag Largest lag to return, in steps

Value

Data frame with lag ($-\text{max_lag}$ to max_lag) and r

Examples

```
rain <- sin(1:48 / 2)  
searches <- c(rain[-1], 0)  
cross_correlation(searches, rain, max_lag = 3)
```

CRUTSBbox

Download CRU TS climate data for a bounding box

Description

Downloads CRU TS v4.07 monthly gridded climate data and filters the data to a geographic bounding box. The data is for the global land areas at a resolution of 0.5 degrees, for 1901-2022.

Usage

```
CRUTSBbox(...)

cru_ts_bbox(
  variable,
  start_year,
  end_year,
  north,
  south,
  east,
  west,
  output_dir = tempdir(),
  use_cache = TRUE,
  ...
)
```

Arguments

...	Arguments that the aliases send to the primary function.
variable	CRU TS variable code. See list_cru_ts_variables() . Common values: "tmp" (mean temperature), "pre" (precipitation), "tmx" (max temperature), "tmn" (min temperature).
start_year	Start year (1901-2022).
end_year	End year (1901-2022).
north	North boundary (latitude).
south	South boundary (latitude).
east	East boundary (longitude).
west	West boundary (longitude).
output_dir	Directory for temporary files (default: tempdir()).
use_cache	If TRUE, use the data in the cache (default: TRUE).

Value

A data.frame with the columns: year, month, latitude, longitude, value, variable.

Examples

```
# Monthly mean temperature for India, 2010-2020
data <- cru_ts_bbox(
  variable = "tmp",
  start_year = 2010, end_year = 2020,
  north = 35, south = 8, east = 97, west = 68
)

# Precipitation for Europe, 1981-2010
data <- cru_ts_bbox(
  variable = "pre",
  start_year = 1981, end_year = 2010,
  north = 71, south = 36, east = 40, west = -10
)
```

CRUTSGeojson

Download CRU TS climate data for a GeoJSON region

Description

Downloads CRU TS v4.07 monthly gridded climate data and filters the data to a geographic region. A GeoJSON polygon defines the region.

Usage

```
CRUTSGeojson(...)

cru_ts_geojson(
  variable,
  start_year,
  end_year,
  geojson_file,
  output_dir = tempdir(),
  use_cache = TRUE,
  ...
)
```

Arguments

...	Arguments that the aliases send to the primary function.
variable	CRU TS variable code. See list_cru_ts_variables() .
start_year	Start year (1901-2022).
end_year	End year (1901-2022).
geojson_file	Path to a GeoJSON file that defines the region.
output_dir	Directory for temporary files (default: tempdir()).
use_cache	If TRUE, use the data in the cache (default: TRUE).

Value

A data.frame with the columns: year, month, latitude, longitude, value, variable.

Examples

```
region <- system.file("extdata", "region.geojson", package = "varunayan")
data <- cru_ts_geojson(
  variable = "tmp",
  start_year = 1981, end_year = 2010,
  geojson_file = region
)
```

DescribeVariables

Describe ERA5 variables in detail

Description

Describe ERA5 variables in detail

Usage

```
DescribeVariables(...)
```

```
describe_variables(variables, dataset_type = "all")
```

Arguments

<code>...</code>	Arguments that the aliases send to the primary function.
<code>variables</code>	Character vector of variable names to describe
<code>dataset_type</code>	Character string that gives the dataset type ("single", "pressure", or "all")

Value

A data.frame with columns variable_name, description, units, dataset_type and category, one row per matched variable.

Examples

```
# Describe specific variables
descriptions <- describe_variables(c("2m_temperature", "total_precipitation"))

# Get descriptions for pressure level variables
pressure_desc <- describe_variables("temperature", dataset_type = "pressure")
```

`dewpoint_from_relative_humidity`*Calculate dewpoint from temperature and relative humidity*

Description

This is the inverse of `relative_humidity_from_dewpoint()` (same Magnus constants), so the two functions give back the input.

Usage

```
dewpoint_from_relative_humidity(temp_c, rh)
```

Arguments

<code>temp_c</code>	Air temperature in Celsius
<code>rh</code>	Relative humidity as a percentage (0-100]

Value

Dewpoint temperature in Celsius

Examples

```
dewpoint_from_relative_humidity(30, 60)
```

`download_era5_pressure`*Download ERA5 pressure-level data with ecmwfr*

Description

Download ERA5 pressure-level data with ecmwfr

Usage

```
download_era5_pressure(  
  variables,  
  pressure_levels,  
  start_date,  
  end_date,  
  area = NULL,  
  resolution = 0.25,  
  frequency = "hourly",  
  output_file,  
  use_cache = TRUE,  
  verbose = FALSE  
)
```

Arguments

variables	Character vector of variable names
pressure_levels	Character vector of pressure levels (e.g., c("1000", "850", "500"))
start_date	Date object or character string (YYYY-MM-DD)
end_date	Date object or character string (YYYY-MM-DD)
area	Numeric vector of 4 elements: c(north, west, south, east) in decimal degrees
resolution	Numeric value for grid resolution (default: 0.25 degrees)
frequency	Character string: "hourly", "daily", "monthly"
output_file	Character string path for output NetCDF file
use_cache	If TRUE, use cached data when it is available (default: TRUE)
verbose	Logical. If TRUE, print progress messages

Value

Character string path to downloaded file

download_era5_single *Download ERA5 single-level data with ecmwfr*

Description

Download ERA5 single-level data with ecmwfr

Usage

```
download_era5_single(
  variables,
  start_date,
  end_date,
  area = NULL,
  resolution = 0.25,
  frequency = "hourly",
  output_file,
  timeout = 3600,
  retry_attempts = 5,
  use_cache = TRUE,
  verbose = FALSE
)
```

Arguments

variables	Character vector of variable names
start_date	Date object or character string (YYYY-MM-DD)
end_date	Date object or character string (YYYY-MM-DD)
area	Numeric vector of 4 elements: c(north, west, south, east) in decimal degrees
resolution	Numeric value for grid resolution (default: 0.25 degrees)
frequency	Character string: "hourly", "daily", "monthly"
output_file	Character string path for output NetCDF file
timeout	Numeric value for request timeout in seconds (default: 3600)
retry_attempts	Integer number of retry attempts (default: 5)
use_cache	If TRUE, use cached data when it is available (default: TRUE)
verbose	Logical. If TRUE, print progress messages

Value

Character string path to downloaded file

download_imd_rainfall *Download IMD gridded rainfall data*

Description

Downloads daily gridded rainfall data from IMD at the specified resolution.

Usage

```
download_imd_rainfall(
  start_year,
  end_year,
  resolution = 0.25,
  output_dir = tempdir(),
  use_cache = TRUE
)
```

Arguments

start_year	Start year.
end_year	End year.
resolution	Spatial resolution: 0.25 or 1.0 degrees.
output_dir	Directory for the downloaded files.
use_cache	If TRUE, use the cached data when it is available (default: TRUE).

Value

Character vector of the paths to the downloaded files.

Examples

```
# Download 0.25 degree rainfall for 2023-2025
files <- download_imd_rainfall(
  start_year = 2023,
  end_year = 2025,
  resolution = 0.25
)
```

download_imd_temperature

Download IMD gridded temperature data

Description

Downloads daily gridded temperature data (maximum or minimum) from IMD. Temperature data is available only at 1.0 degree resolution.

Usage

```
download_imd_temperature(
  start_year,
  end_year,
  var_type = "tmax",
  output_dir = tempdir(),
  use_cache = TRUE
)
```

Arguments

start_year	Start year.
end_year	End year.
var_type	Type of temperature: "tmax" or "tmin".
output_dir	Directory for the downloaded files.
use_cache	If TRUE, use the cached data when it is available (default: TRUE).

Value

Character vector of the paths to the downloaded files.

Examples

```
# Download maximum temperature for 2023-2025
files <- download_imd_temperature(
  start_year = 2023,
  end_year = 2025,
  var_type = "tmax"
)
```

ensure_output_dir	Create the output directory if it does not exist
-------------------	--

Description

Create the output directory if it does not exist

Usage

```
ensure_output_dir(output_dir)
```

Arguments

output_dir	Path to output directory
------------	--------------------------

Value

Character string. The path to the directory that the function made or found

ERA5ifyBbox	Download and process ERA5 data for a bounding box
-------------	---

Description

Download and process ERA5 data for a bounding box

Usage

```
ERA5ifyBbox(...)

era5ify_bbox(
  request_id,
  variables,
  start_date,
  end_date,
  north,
  south,
```

```

    east,
    west,
    dataset_type = "single",
    pressure_levels = NULL,
    frequency = "hourly",
    resolution = 0.25,
    save_raw = FALSE,
    output_dir = tempdir(),
    use_cache = TRUE,
    convert_units = TRUE,
    verbose = FALSE
)

```

Arguments

...	Arguments passed to the main function (used by aliases).
request_id	Unique identifier for the data request.
variables	List of ERA5 variables to download.
start_date	Start date in "YYYY-MM-DD" format.
end_date	End date in "YYYY-MM-DD" format.
north	Northern latitude boundary.
south	Southern latitude boundary.
east	Eastern longitude boundary.
west	Western longitude boundary.
dataset_type	Type of dataset ("single" or "pressure").
pressure_levels	Pressure levels for pressure dataset.
frequency	Temporal frequency ("hourly", "daily", "monthly").
resolution	Spatial resolution in degrees (default: 0.25).
save_raw	If TRUE, save the raw downloaded files.
output_dir	Directory for the saved files (default: tempdir()).
use_cache	If TRUE, use cached data when it is available (default: TRUE).
convert_units	If TRUE, convert units to user-friendly formats (default: TRUE). When TRUE, the function returns temperature variables in Celsius (converted from Kelvin). It returns precipitation variables in mm (converted from meters).
verbose	If TRUE, print detailed progress messages.

Value

data.frame with processed climate data. When `convert_units = TRUE`:

- Temperature variables (e.g., `2m_temperature`): Celsius
- Precipitation variables (e.g., `total_precipitation`): mm
- Other variables: original ERA5 units

Examples

```

setup_cds_credentials(key = "your-cds-api-key")

data <- era5ify_bbox(
  request_id = "my_request",
  variables = c("2m_temperature", "total_precipitation"),
  start_date = "2023-01-01",
  end_date = "2023-01-31",
  north = 40, south = 35, east = -70, west = -75
)
# Temperature is in Celsius. Precipitation is in mm.

```

ERA5ifyPoint

*Download and process ERA5 data for a point location***Description**

Download and process ERA5 data for a point location

Usage

```

ERA5ifyPoint(...)

era5ify_point(
  request_id,
  variables,
  start_date,
  end_date,
  lat,
  lon,
  dataset_type = "single",
  pressure_levels = NULL,
  frequency = "hourly",
  save_raw = FALSE,
  output_dir = tempdir(),
  use_cache = TRUE,
  convert_units = TRUE,
  verbose = FALSE,
  use_timeseries_api = NA
)

```

Arguments

...	Arguments passed to the main function (used by aliases).
request_id	Unique identifier for the data request.
variables	List of ERA5 variables to download.

<code>start_date</code>	Start date in "YYYY-MM-DD" format.
<code>end_date</code>	End date in "YYYY-MM-DD" format.
<code>lat</code>	Latitude of the point location.
<code>lon</code>	Longitude of the point location.
<code>dataset_type</code>	Type of dataset ("single" or "pressure").
<code>pressure_levels</code>	Pressure levels for pressure dataset.
<code>frequency</code>	Temporal frequency ("hourly", "daily", "monthly").
<code>save_raw</code>	If TRUE, save the raw downloaded files.
<code>output_dir</code>	Directory for the saved files (default: <code>tempdir()</code>).
<code>use_cache</code>	If TRUE, use cached data when it is available (default: TRUE).
<code>convert_units</code>	If TRUE, convert units to user-friendly formats (default: TRUE). When TRUE, the function returns temperature variables in Celsius (converted from Kelvin). It returns precipitation variables in mm (converted from meters).
<code>verbose</code>	If TRUE, print detailed progress messages.
<code>use_timeseries_api</code>	If TRUE, use the CDS time-series endpoint. This endpoint gives the data for a point directly. It is much faster than a subset of a gridded download. The default is NA: use the endpoint only for hourly single-level requests, because the endpoint supports only these requests. Set FALSE to always use the gridded download. If the endpoint is not available, the function automatically uses the gridded download.

Value

data.frame with processed climate data. When `convert_units = TRUE`:

- Temperature variables (e.g., `2m_temperature`): Celsius
- Precipitation variables (e.g., `total_precipitation`): mm
- Other variables: original ERA5 units

Examples

```
setup_cds_credentials(key = "your-cds-api-key")

data <- era5ify_point(
  request_id = "my_request",
  variables = c("2m_temperature", "total_precipitation"),
  start_date = "2023-01-01",
  end_date = "2023-01-31",
  lat = 40.7128,
  lon = -74.0060
)
# Temperature is in Celsius. Precipitation is in mm.
```

excess_heat_factor	<i>Excess Heat Factor</i>
--------------------	---------------------------

Description

Excess Heat Factor (EHF) of Nairn & Fawcett (2015). Daily mean temperature (DMT) pairs each day's maximum with the following night's minimum, $T_i = (tmax_i + tmin_{(i+1)}) / 2$. For the three-day period starting on day i , $EHI_sig = mean(T_i, T_{i+1}, T_{i+2}) - T95$ and $EHI_accl = mean(T_i, T_{i+1}, T_{i+2}) - mean(T_{i-1}, \dots, T_{i-30})$, with $T95$ the 95th percentile of DMT over the baseline years; $EHF = EHI_sig * max(1, EHI_accl)$. Positive EHF marks heatwave conditions; EHF85, the 85th percentile of positive baseline EHF values, is the severe threshold and $3 * EHF85$ the extreme threshold.

Usage

`excess_heat_factor(date, tmax, tmin, baseline)`

Arguments

- `date` Dates of a strictly increasing daily series for one location. Missing days leave the windows that span them NA.
- `tmax, tmin` Daily maximum and minimum temperature (degrees Celsius).
- `baseline` Climatology years, `c(first, last)`.

Value

A data.frame with `date`, `dmt`, `ehi_sig`, `ehi_accl` and `ehf` (degrees Celsius squared), indexed by the first day of each three-day period, with attributes `t95` and `ehf85`. NA where the windows are incomplete.

References

Nairn, J.R. & Fawcett, R.J.B. (2015). The Excess Heat Factor: A Metric for Heatwave Intensity and Its Use in Classifying Heatwave Severity. *International Journal of Environmental Research and Public Health*, 12(1), 227-253. [doi:10.3390/ijerph120100227](https://doi.org/10.3390/ijerph120100227)

Examples

```
d <- seq(as.Date("2001-01-01"), as.Date("2003-12-31"), by = "day")
doy <- as.POSIXlt(d)$yday
tmax <- 33 + 8 * sin(2 * pi * (doy - 80) / 365)
tmax[d >= as.Date("2003-05-10") & d <= as.Date("2003-05-16")] <- 47
ehf <- excess_heat_factor(d, tmax, tmax - 12, baseline = c(2001, 2002))
subset(ehf, ehf > 0 & date > as.Date("2003-05-01") & date < as.Date("2003-05-31"))
```

exclude_cols	<i>Columns to exclude from aggregation</i>
--------------	--

Description

Aggregation does not apply to these coordinate and metadata columns.

Usage

```
exclude_cols
```

Value

A character vector of variable names.

Examples

```
head(exclude_cols)
```

exposure_indicators	<i>Heat exposure indicators</i>
---------------------	---------------------------------

Description

Summarizes daily temperature (and optionally humidity) into heat exposure indicators per location and year or month, as used in heat-health vulnerability indices: heatwave and warm-night frequency and duration, diurnal temperature range, WBGT, heat index and wet-bulb temperature, plus the ETCCDI indices TX90p, TN90p, WSDI and tropical nights.

Usage

```
exposure_indicators(
  data,
  by = c("latitude", "longitude"),
  period = c("year", "month"),
  months = NULL,
  baseline = c(1991, 2020),
  heatwave_method = c("imd", "percentile", "ehf"),
  warm_night_method = c("imd", "percentile", "absolute"),
  terrain = c("auto", "plains", "coastal", "hilly"),
  hill_elevation = 1200,
  cell_size = NULL
)
```

Arguments

<code>data</code>	A data.frame of daily values; see Details.
<code>by</code>	Columns identifying a location, or NULL for a single series.
<code>period</code>	Summarize by "year" or "month".
<code>months</code>	Months (1-12) to include, e.g. 3:6 for the Indian hot season; NULL for all.
<code>baseline</code>	Climatology years, <code>c(first, last)</code> , for normals and percentiles.
<code>heatwave_method</code>	Passed to <code>heatwave_days()</code> as method.
<code>warm_night_method</code>	Passed to <code>warm_nights()</code> as method.
<code>terrain</code>	Passed to <code>heatwave_days()</code> for the IMD definition. "auto" classifies each location with <code>imd_terrain()</code> from its latitude and longitude columns and adds a terrain column.
<code>hill_elevation, cell_size</code>	Passed to <code>imd_terrain()</code> when <code>terrain = "auto"</code> .

Details

`data` needs columns `date`, `tmax` and `tmin` (degrees Celsius), one row per day per location, covering the baseline years. With a `dewpoint` column (degrees Celsius), afternoon humidity metrics are computed from `tmax` and `dewpoint`: WBGT by `wbgt_simple()`, heat index and wet-bulb temperature. A `wbgt` column, such as daily maxima of `wbgt_liljegren()`, replaces the `wbgt_simple()` estimate.

Spells are found on the full series, so a heatwave spanning two periods counts as an event in the period where it starts and its days count where they fall. `months` filters the summary.

Value

A data.frame with one row per location and period and columns:

n_days days with data

tmax_mean, tmin_mean mean daily maximum and minimum temperature

dtr_mean mean diurnal temperature range (ETCCDI DTR)

hot_days days with Tmax of at least 40 C

tropical_nights nights with Tmin above 20 C (ETCCDI TR)

tx90p, tn90p percent of days above the calendar-day 90th percentile of Tmax and Tmin

wsdi days in runs of at least 6 days with Tmax above its 90th percentile (ETCCDI WSDI)

heatwave_days, heatwave_events, heatwave_longest, severe_heatwave_days heatwave duration (total days), frequency (events starting in the period), longest event and severe days, from `heatwave_days()`

warm_nights, warm_night_spells, warm_night_longest, very_warm_nights the same for `warm_nights()`

With humidity: `wbgt_mean`, `wbgt_max`, `wbgt_days_high` (WBGT of at least 29.4 C, 85 F) and `wbgt_days_extreme` (at least 31.1 C, 88 F), `heat_index_max`, `heat_index_days_danger` (at least 39.4 C, 103 F), `wet_bulb_max` and `wet_bulb_days_31` (wet bulb of at least 31 C, near the 30.55 C mean critical limit of Vecellio et al. 2022).

References

Vecellio, D.J., Wolf, S.T., Cottle, R.M. & Kenney, W.L. (2022). Evaluating the 35 C wet-bulb temperature adaptability threshold for young, healthy subjects (PSU HEAT Project). *Journal of Applied Physiology*, 132(2), 340-345. doi:10.1152/jappphysiol.00738.2021

See Also

[imd_exposure_bbox\(\)](#) to download IMD data and compute these in one call; [ndvi\(\)](#) and [ndbi\(\)](#) for the land-surface indicators.

Examples

```
d <- seq(as.Date("2001-01-01"), as.Date("2004-12-31"), by = "day")
doy <- as.POSIXlt(d)$yday
tmax <- 33 + 8 * sin(2 * pi * (doy - 80) / 365)
tmax[d >= as.Date("2004-05-10") & d <= as.Date("2004-05-14")] <- 46.5
daily <- data.frame(date = d, tmax = tmax, tmin = tmax - 13, dewpoint = 18)
exposure_indicators(daily, by = NULL, baseline = c(2001, 2003), terrain = "plains")

# Jaipur: terrain looked up from the coordinates
daily$latitude <- 26.9
daily$longitude <- 75.8
exposure_indicators(daily, baseline = c(2001, 2003))
```

extract_point_data	<i>Extract data for a specified point location (nearest neighbor)</i>
--------------------	---

Description

Extract data for a specified point location (nearest neighbor)

Usage

```
extract_point_data(netcdf_file, target_lat, target_lon)
```

Arguments

netcdf_file	Path to the NetCDF file, as a character string
target_lat	Target latitude
target_lon	Target longitude

Value

data.frame with data for the nearest point

```
filter_dataframe_by_geojson
```

Filter data.frame by GeoJSON polygon

Description

This function does a test of only the unique (lat, lon) coordinates against the polygon. Then it joins the result to the full dataset with a data.table keyed semi-join.

Usage

```
filter_dataframe_by_geojson(df, geojson_file)
```

Arguments

df	data.frame with latitude and longitude columns
geojson_file	Character string path to GeoJSON file

Value

data.frame with spatially filtered data

```
filter_imd_by_bbox
```

Filter IMD data by spatial boundaries

Description

Filter IMD data by spatial boundaries

Usage

```
filter_imd_by_bbox(data, north, south, east, west)
```

Arguments

data	data.frame with IMD data
north	Latitude of the north boundary
south	Latitude of the south boundary
east	Longitude of the east boundary
west	Longitude of the west boundary

Value

The input data.frame restricted to rows whose latitude/longitude fall inside the region; columns are unchanged.

Examples

```
imd <- data.frame(  
  date = rep(as.Date("2023-01-01") + 0:59, each = 2),  
  latitude = 20.5, longitude = c(73.5, 79.5), rainfall = 1  
)  
filter_imd_by_bbox(imd, north = 22, south = 18, east = 76, west = 72)
```

filter_imd_by_geojson *Filter IMD data by GeoJSON polygon*

Description

Filter IMD data by GeoJSON polygon

Usage

```
filter_imd_by_geojson(data, geojson_file)
```

Arguments

data	data.frame with IMD data
geojson_file	Path to the GeoJSON file

Value

The input data.frame restricted to rows whose latitude/longitude fall inside the region; columns are unchanged.

Examples

```
imd <- data.frame(  
  date = rep(as.Date("2023-01-01") + 0:59, each = 2),  
  latitude = 20.5, longitude = c(73.5, 79.5), rainfall = 1  
)  
region <- system.file("extdata", "region.geojson", package = "varunayan")  
filter_imd_by_geojson(imd, region)
```

filter_netcdf_by_bbox *Filter NetCDF data by spatial boundaries (bounding box)*

Description

Filter NetCDF data by spatial boundaries (bounding box)

Usage

```
filter_netcdf_by_bbox(netcdf_file, north, south, east, west)
```

Arguments

netcdf_file	Path to the NetCDF file, as a character string
north	Northern latitude boundary
south	Southern latitude boundary
east	Eastern longitude boundary
west	Western longitude boundary

Value

data.frame with spatially filtered data

filter_netcdf_by_geojson
Filter NetCDF data by GeoJSON polygon

Description

Filter NetCDF data by GeoJSON polygon

Usage

```
filter_netcdf_by_geojson(netcdf_file, geojson_file)
```

Arguments

netcdf_file	Path to the NetCDF file, as a character string
geojson_file	Character string path to GeoJSON file

Value

data.frame with spatially filtered data

<code>format_date_range</code>	<i>Format date range for CDS API requests</i>
--------------------------------	---

Description

Format date range for CDS API requests

Usage

`format_date_range(start_date, end_date)`

Arguments

- `start_date` Start date (Date object)
- `end_date` End date (Date object)

Value

Character vector of date strings in YYYY-MM-DD format

<code>format_pressure_levels</code>	<i>Convert pressure levels to the character format necessary for the CDS API</i>
-------------------------------------	--

Description

Convert pressure levels to the character format necessary for the CDS API

Usage

`format_pressure_levels(pressure_levels)`

Arguments

- `pressure_levels`
Numeric or character vector of pressure levels

Value

Character vector of pressure levels

`GetAvailablePressureLevels`*Get the standard pressure levels that are available in ERA5*

Description

Get the standard pressure levels that are available in ERA5

Usage

```
GetAvailablePressureLevels(...)
```

```
get_available_pressure_levels()
```

Arguments

... Arguments that the aliases send to the primary function.

Value

Character vector of pressure levels in hPa

Examples

```
get_available_pressure_levels()
```

`GetCacheDir`*Get cache directory path*

Description

Defaults to `tools::R_user_dir("varunayan", "cache")`. Set the option `varunayan.cache_dir` to use a different directory.

Usage

```
GetCacheDir(...)
```

```
get_cache_dir(create = TRUE)
```

Arguments

... Arguments for the main function (for use by aliases).

`create` Create the directory when it does not exist (default: TRUE)

Value

Character string with cache directory path

Examples

```
get_cache_dir(create = FALSE)
```

GetERA5CountryTemperature

Get ERA5 temperature data for a country

Description

Downloads ERA5 temperature data for a country and aggregates the data. The function finds the country boundary and downloads monthly data with [era5ify_geojson\(\)](#). It returns country-level averages for each year and month, with area weights (cosine of latitude).

Usage

```
GetERA5CountryTemperature(...)
```

```
get_era5_country_temperature(
  country,
  start_date,
  end_date,
  variables = "mean",
  request_id = NULL,
  resolution = 0.25,
  verbose = FALSE,
  ...
)
```

Arguments

...	More arguments that the function sends to era5ify_geojson() .
country	One of: a country name string (the function uses <code>maps::map()</code> to find it), a path to a GeoJSON file, or an <code>sf</code> object. The function automatically accepts common aliases, for example "USA" and "UK".
start_date	Start date in "YYYY-MM-DD" format.
end_date	End date in "YYYY-MM-DD" format.
variables	Character vector of temperature shorthand names or ERA5 variable names. Short-hands: "mean" (2m_temperature), "max" (maximum_2m_temperature_since_previous_post_processing), "min" (minimum_2m_temperature_since_previous_post_processing). Default: "mean".
request_id	Optional request identifier. If you do not supply it, the function makes it from the country name.

resolution Spatial resolution in degrees (default: 0.25).
 verbose If TRUE, show detailed progress messages.

Value

A data.frame with the columns year, month, and one column for each requested variable (for example, temperature_mean, temperature_max, temperature_min). The temperature values are in Celsius.

Examples

```
# Monthly mean temperature for India
get_era5_country_temperature("India", "2023-06-01", "2023-06-30")

# Mean and max temperature for the USA
get_era5_country_temperature("USA", "2023-01-01", "2023-12-31",
  variables = c("mean", "max")
)

# Use an sf object directly
library(sf)
poly <- st_read("my_country.geojson")
get_era5_country_temperature(poly, "2023-01-01", "2023-06-30")
```

GetERA5DailyClimate *Download daily ERA5 climate data*

Description

This function downloads ERA5 climate variables (temperature, humidity, wet bulb, wind, solar radiation) for a region.

Usage

```
GetERA5DailyClimate(
  request_id,
  start_date,
  end_date,
  variables = c("temperature", "humidity"),
  json_file = NULL,
  north = NULL,
  south = NULL,
  east = NULL,
  west = NULL,
  resolution = 0.25,
  use_cache = TRUE,
  verbose = FALSE
```

```

)

get_era5_daily_climate(
  request_id,
  start_date,
  end_date,
  variables = c("temperature", "humidity"),
  json_file = NULL,
  north = NULL,
  south = NULL,
  east = NULL,
  west = NULL,
  resolution = 0.25,
  use_cache = TRUE,
  verbose = FALSE
)

```

Arguments

<code>request_id</code>	Unique identifier for the data request
<code>start_date</code>	Start date in "YYYY-MM-DD" format
<code>end_date</code>	End date in "YYYY-MM-DD" format
<code>variables</code>	Character vector of variables to download. Options: "temperature", "humidity", "wet_bulb", "wind", "solar"
<code>json_file</code>	Path to the GeoJSON file that defines the region
<code>north, south, east, west</code>	Bounding box coordinates (alternative to <code>json_file</code>)
<code>resolution</code>	Spatial resolution in degrees (default: 0.25)
<code>use_cache</code>	If TRUE, the function uses cached data (default: TRUE)
<code>verbose</code>	If TRUE, the function prints progress messages (default: FALSE)

Value

data.frame with date, latitude, longitude, and requested variables

Examples

```

region <- system.file("extdata", "region.geojson", package = "varunayan")
# Get temperature and humidity
climate <- GetERA5DailyClimate(
  request_id = "india_climate",
  start_date = "2023-05-01",
  end_date = "2023-05-31",
  variables = c("temperature", "humidity"),
  json_file = region
)

```

`GetERA5DailyHeatIndexData`*Download ERA5 data and calculate heat stress indices*

Description

This function downloads ERA5 temperature, dewpoint, and wind data for a region. Then it calculates the heat stress indices.

Usage

```
GetERA5DailyHeatIndexData(  
  request_id,  
  start_date,  
  end_date,  
  json_file = NULL,  
  north = NULL,  
  south = NULL,  
  east = NULL,  
  west = NULL,  
  solar_load = FALSE,  
  resolution = 0.25,  
  use_cache = TRUE,  
  verbose = FALSE  
)
```

```
get_era5_daily_heat_index_data(  
  request_id,  
  start_date,  
  end_date,  
  json_file = NULL,  
  north = NULL,  
  south = NULL,  
  east = NULL,  
  west = NULL,  
  solar_load = FALSE,  
  resolution = 0.25,  
  use_cache = TRUE,  
  verbose = FALSE  
)
```

```
GetERA5DailyHeatData(  
  request_id,  
  start_date,  
  end_date,  
  json_file = NULL,  
  north = NULL,
```

```

    south = NULL,
    east = NULL,
    west = NULL,
    solar_load = FALSE,
    resolution = 0.25,
    use_cache = TRUE,
    verbose = FALSE
)

get_era5_daily_heat_data(
  request_id,
  start_date,
  end_date,
  json_file = NULL,
  north = NULL,
  south = NULL,
  east = NULL,
  west = NULL,
  solar_load = FALSE,
  resolution = 0.25,
  use_cache = TRUE,
  verbose = FALSE
)

```

Arguments

<code>request_id</code>	Unique identifier for the data request
<code>start_date</code>	Start date in "YYYY-MM-DD" format
<code>end_date</code>	End date in "YYYY-MM-DD" format
<code>json_file</code>	Path to the GeoJSON file that defines the region (for the geojson method)
<code>north</code>	Northern latitude boundary (for the bbox method)
<code>south</code>	Southern latitude boundary (for the bbox method)
<code>east</code>	Eastern longitude boundary (for the bbox method)
<code>west</code>	Western longitude boundary (for the bbox method)
<code>solar_load</code>	If TRUE, include solar radiation in the calculations (default: FALSE). If TRUE, the function downloads solar radiation data and uses these data for WBGT and UTCI.
<code>resolution</code>	Spatial resolution in degrees (default: 0.25)
<code>use_cache</code>	If TRUE, the function uses cached data when the data is available (default: TRUE)
<code>verbose</code>	If TRUE, the function prints progress messages (default: FALSE)

Value

data.frame with columns: date, latitude, longitude, temp_c, dewpoint_c, wind_speed, rh, wet_bulb, heat_index, wbgt, utci, humidex, wbgt_risk, heat_index_risk, utci_stress. If solar_load=TRUE, the data.frame also contains solar_radiation.

Examples

```
region <- system.file("extdata", "region.geojson", package = "varunayan")
heat_data <- GetERA5DailyHeatIndexData(
  request_id = "india_heat_2023",
  start_date = "2023-05-01",
  end_date = "2023-05-31",
  json_file = region
)

# With solar radiation for outdoor WBGT
heat_data <- GetERA5DailyHeatIndexData(
  request_id = "india_heat_2023_solar",
  start_date = "2023-05-01",
  end_date = "2023-05-31",
  json_file = region,
  solar_load = TRUE
)
```

GetERA5DailyHumidity *Download daily ERA5 humidity data*

Description

This function downloads temperature and dewpoint data. Then it calculates the relative humidity.

Usage

```
GetERA5DailyHumidity(
  request_id,
  start_date,
  end_date,
  json_file = NULL,
  north = NULL,
  south = NULL,
  east = NULL,
  west = NULL,
  resolution = 0.25,
  use_cache = TRUE,
  verbose = FALSE
)

get_era5_daily_humidity(
  request_id,
  start_date,
  end_date,
  json_file = NULL,
  north = NULL,
```

```

    south = NULL,
    east = NULL,
    west = NULL,
    resolution = 0.25,
    use_cache = TRUE,
    verbose = FALSE
  )

```

Arguments

request_id	Unique identifier for the data request
start_date	Start date in "YYYY-MM-DD" format
end_date	End date in "YYYY-MM-DD" format
json_file	Path to the GeoJSON file that defines the region
north, south, east, west	Bounding box coordinates (alternative to json_file)
resolution	Spatial resolution in degrees (default: 0.25)
use_cache	If TRUE, the function uses cached data (default: TRUE)
verbose	If TRUE, the function prints progress messages (default: FALSE)

Value

data.frame with date, latitude, longitude, temp_c, dewpoint_c, rh

Examples

```

region <- system.file("extdata", "region.geojson", package = "varunayan")
humidity <- GetERA5DailyHumidity(
  request_id = "india_humidity",
  start_date = "2023-05-01",
  end_date = "2023-05-31",
  json_file = region
)

```

GetERA5DailyTemperature

Download daily ERA5 temperature data

Description

Download daily ERA5 temperature data

Usage

```

GetERA5DailyTemperature(
  request_id,
  start_date,
  end_date,
  json_file = NULL,
  north = NULL,
  south = NULL,
  east = NULL,
  west = NULL,
  resolution = 0.25,
  use_cache = TRUE,
  verbose = FALSE
)

get_era5_daily_temperature(
  request_id,
  start_date,
  end_date,
  json_file = NULL,
  north = NULL,
  south = NULL,
  east = NULL,
  west = NULL,
  resolution = 0.25,
  use_cache = TRUE,
  verbose = FALSE
)

```

Arguments

<code>request_id</code>	Unique identifier for the data request
<code>start_date</code>	Start date in "YYYY-MM-DD" format
<code>end_date</code>	End date in "YYYY-MM-DD" format
<code>json_file</code>	Path to the GeoJSON file that defines the region
<code>north, south, east, west</code>	Bounding box coordinates (alternative to <code>json_file</code>)
<code>resolution</code>	Spatial resolution in degrees (default: 0.25)
<code>use_cache</code>	If TRUE, the function uses cached data (default: TRUE)
<code>verbose</code>	If TRUE, the function prints progress messages (default: FALSE)

Value

data.frame with date, latitude, longitude, temp_c

Examples

```
region <- system.file("extdata", "region.geojson", package = "varunayan")
temp <- GetERA5DailyTemperature(
  request_id = "india_temp",
  start_date = "2023-05-01",
  end_date = "2023-05-31",
  json_file = region
)
```

GetERA5DailyWetBulb	<i>Download daily ERA5 wet bulb temperature data</i>
---------------------	--

Description

This function downloads temperature and dewpoint data. Then it calculates RH and the wet bulb temperature.

Usage

```
GetERA5DailyWetBulb(
  request_id,
  start_date,
  end_date,
  json_file = NULL,
  north = NULL,
  south = NULL,
  east = NULL,
  west = NULL,
  resolution = 0.25,
  use_cache = TRUE,
  verbose = FALSE
)

get_era5_daily_wet_bulb(
  request_id,
  start_date,
  end_date,
  json_file = NULL,
  north = NULL,
  south = NULL,
  east = NULL,
  west = NULL,
  resolution = 0.25,
  use_cache = TRUE,
  verbose = FALSE
)
```

Arguments

request_id	Unique identifier for the data request
start_date	Start date in "YYYY-MM-DD" format
end_date	End date in "YYYY-MM-DD" format
json_file	Path to the GeoJSON file that defines the region
north, south, east, west	Bounding box coordinates (alternative to json_file)
resolution	Spatial resolution in degrees (default: 0.25)
use_cache	If TRUE, the function uses cached data (default: TRUE)
verbose	If TRUE, the function prints progress messages (default: FALSE)

Value

data.frame with date, latitude, longitude, temp_c, dewpoint_c, rh, wet_bulb

Examples

```
region <- system.file("extdata", "region.geojson", package = "varunayan")
wetbulb <- GetERA5DailyWetBulb(
  request_id = "india_wetbulb",
  start_date = "2023-05-01",
  end_date = "2023-05-31",
  json_file = region
)
```

GetERA5DailyWind

Download daily ERA5 wind data

Description

This function downloads the 10m wind components. Then it calculates the wind speed.

Usage

```
GetERA5DailyWind(
  request_id,
  start_date,
  end_date,
  json_file = NULL,
  north = NULL,
  south = NULL,
  east = NULL,
  west = NULL,
  resolution = 0.25,
```

```

    use_cache = TRUE,
    verbose = FALSE
  )

  get_era5_daily_wind(
    request_id,
    start_date,
    end_date,
    json_file = NULL,
    north = NULL,
    south = NULL,
    east = NULL,
    west = NULL,
    resolution = 0.25,
    use_cache = TRUE,
    verbose = FALSE
  )

```

Arguments

<code>request_id</code>	Unique identifier for the data request
<code>start_date</code>	Start date in "YYYY-MM-DD" format
<code>end_date</code>	End date in "YYYY-MM-DD" format
<code>json_file</code>	Path to the GeoJSON file that defines the region
<code>north, south, east, west</code>	Bounding box coordinates (alternative to <code>json_file</code>)
<code>resolution</code>	Spatial resolution in degrees (default: 0.25)
<code>use_cache</code>	If TRUE, the function uses cached data (default: TRUE)
<code>verbose</code>	If TRUE, the function prints progress messages (default: FALSE)

Value

data.frame with date, latitude, longitude, wind_speed

Examples

```

region <- system.file("extdata", "region.geojson", package = "varunayan")
wind <- GetERA5DailyWind(
  request_id = "india_wind",
  start_date = "2023-05-01",
  end_date = "2023-05-31",
  json_file = region
)

```

`GetERA5MonthlyHeatIndexData`*Get monthly ERA5 heat stress index data*

Description

This function downloads ERA5 heat stress indices and aggregates them to the specified month.

Usage

```
GetERA5MonthlyHeatIndexData(  
  request_id,  
  year,  
  month,  
  json_file = NULL,  
  north = NULL,  
  south = NULL,  
  east = NULL,  
  west = NULL,  
  solar_load = FALSE,  
  resolution = 0.25,  
  use_cache = TRUE,  
  verbose = FALSE  
)  
  
get_era5_monthly_heat_index_data(  
  request_id,  
  year,  
  month,  
  json_file = NULL,  
  north = NULL,  
  south = NULL,  
  east = NULL,  
  west = NULL,  
  solar_load = FALSE,  
  resolution = 0.25,  
  use_cache = TRUE,  
  verbose = FALSE  
)  
  
GetERA5MonthlyHeatData(  
  request_id,  
  year,  
  month,  
  json_file = NULL,  
  north = NULL,  
  south = NULL,
```

```

    east = NULL,
    west = NULL,
    solar_load = FALSE,
    resolution = 0.25,
    use_cache = TRUE,
    verbose = FALSE
  )

get_era5_monthly_heat_data(
  request_id,
  year,
  month,
  json_file = NULL,
  north = NULL,
  south = NULL,
  east = NULL,
  west = NULL,
  solar_load = FALSE,
  resolution = 0.25,
  use_cache = TRUE,
  verbose = FALSE
)

```

Arguments

<code>request_id</code>	Unique identifier for the data request
<code>year</code>	Year (for example, 2023)
<code>month</code>	Month (1-12)
<code>json_file</code>	Path to the GeoJSON file that defines the region
<code>north, south, east, west</code>	Bounding box coordinates (alternative to <code>json_file</code>)
<code>solar_load</code>	If TRUE, include solar radiation (default: FALSE)
<code>resolution</code>	Spatial resolution in degrees (default: 0.25)
<code>use_cache</code>	If TRUE, the function uses cached data (default: TRUE)
<code>verbose</code>	If TRUE, the function prints progress messages (default: FALSE)

Value

A data.frame with one row per grid point for the requested month: `year`, `month`, `latitude`, `longitude`, `monthly means of the daily heat stress variables`, and the categorical columns `wbgt_risk`, `heat_index_risk` and `utci_stress`.

Examples

```

region <- system.file("extdata", "region.geojson", package = "varunayan")
heat_may <- GetERA5MonthlyHeatIndexData(
  request_id = "india_may2023",

```

```
    year = 2023,  
    month = 5,  
    json_file = region  
  )
```

`GetPackageInfo`*Get package version information*

Description

Get package version information

Usage

```
GetPackageInfo(...)
```

```
get_package_info()
```

Arguments

... Arguments for the main function (for use by aliases).

Value

The `utils::sessionInfo()` object, invisibly. Called for its side effect of reporting the R version, platform and versions of key dependencies as messages.

Examples

```
get_package_info()
```

`get_available_datasets`*Get available dataset types*

Description

Get available dataset types

Usage

```
get_available_datasets()
```

Value

Character vector of available dataset types

Examples

```
get_available_datasets()
```

get_bbox_from_sf	<i>Get bounding box from sf object</i>
------------------	--

Description

Get bounding box from sf object

Usage

```
get_bbox_from_sf(sf_obj)
```

Arguments

sf_obj	sf object
--------	-----------

Value

Named numeric vector with xmin, ymin, xmax, ymax

get_cds_credentials	<i>Get CDS API credentials from different sources</i>
---------------------	---

Description

Checks the CDS_API_KEY environment variable, then the 'ecmwfr' keyring, then ~/.cdsapirc. A key found in the environment variable or in ~/.cdsapirc is registered with 'ecmwfr' via [ecmwfr::wf_set_key\(\)](#).

Usage

```
get_cds_credentials(silent = FALSE)
```

Arguments

silent	If TRUE, do not show information messages
--------	---

Value

TRUE if credentials are available, FALSE otherwise.

Examples

```
get_cds_credentials()
```

get_imd_grid_specs	<i>Get IMD grid specifications</i>
--------------------	------------------------------------

Description

Returns the grid specifications for an IMD dataset.

Usage

```
get_imd_grid_specs(dataset)
```

Arguments

dataset Dataset identifier: "rainfall_0.25", "rainfall_1.0", "tmax_1.0", "tmin_1.0".

Value

A list with elements nlat, nlon, lat_start, lat_end, lon_start, lon_end, resolution (degrees), unit, missing_value, format and description.

Examples

```
specs <- get_imd_grid_specs("rainfall_0.25")
```

get_pressure_level_variables	<i>Get the dataset of pressure-level variables</i>
------------------------------	--

Description

Get the dataset of pressure-level variables

Usage

```
get_pressure_level_variables()
```

Value

List that contains the pressure-level variable categories

`get_pressure_level_variable_names`*Get all valid pressure-level variable names*

Description

Get all valid pressure-level variable names

Usage

```
get_pressure_level_variable_names()
```

Value

Character vector of valid pressure-level variable names

`get_single_level_variables`*Get the dataset of single-level variables*

Description

Get the dataset of single-level variables

Usage

```
get_single_level_variables()
```

Value

List that contains the single-level variable categories

`get_single_level_variable_names`*Get all valid single-level variable names*

Description

Get all valid single-level variable names

Usage

```
get_single_level_variable_names()
```

Value

Character vector of valid single-level variable names

get_time_values	<i>Get time values for a frequency</i>
-----------------	--

Description

Get time values for a frequency

Usage

```
get_time_values(frequency)
```

Arguments

frequency	Character string that gives the temporal frequency
-----------	--

Value

Character vector of time strings

get_timings	<i>Get all recorded time measurements</i>
-------------	---

Description

Get all recorded time measurements

Usage

```
get_timings()
```

Value

A data.frame with columns label, elapsed_seconds, timestamp and duration (formatted), one row per timed operation; zero rows if nothing has been timed.

Examples

```
get_timings()
```

HadEX3Bbox

*Download HadEX3 data on climate extremes for a bounding box***Description**

Downloads HadEX3 data on ETCCDI climate extremes and filters the data to a geographic bounding box. The data is for 1901-2018 at a resolution of 1.25 x 1.875 degrees.

Usage

```
HadEX3Bbox(...)

hadex3_bbox(
  index,
  start_year,
  end_year,
  north,
  south,
  east,
  west,
  frequency = "annual",
  baseline = "61-90",
  output_dir = tempdir(),
  use_cache = TRUE
)
```

Arguments

<code>...</code>	Arguments that the aliases send to the primary function.
<code>index</code>	ETCCDI index name (e.g. "TXx", "Rx1day"). See list_hadex3_indices() .
<code>start_year</code>	Start year (1901-2018).
<code>end_year</code>	End year (1901-2018).
<code>north</code>	North boundary (latitude).
<code>south</code>	South boundary (latitude).
<code>east</code>	East boundary (longitude).
<code>west</code>	West boundary (longitude).
<code>frequency</code>	Temporal frequency: "annual" or "monthly" (default: "annual").
<code>baseline</code>	Reference period for the indices that use percentiles: "61-90" (default) or "81-10". This argument applies only to the annual frequency.
<code>output_dir</code>	Directory for temporary files (default: <code>tempdir()</code>).
<code>use_cache</code>	If TRUE, use the data in the cache (default: TRUE).

Value

A data.frame with the columns: year (and month for monthly data), latitude, longitude, value, index.

Examples

```
# Annual maximum of the daily maximum temperature for Europe, 1981-2010
data <- hadex3_bbox(
  index = "TXx",
  start_year = 1981, end_year = 2010,
  north = 71, south = 36, east = 40, west = -10
)

# Monthly Rx1day for India
data <- hadex3_bbox(
  index = "Rx1day",
  start_year = 2000, end_year = 2018,
  north = 35, south = 8, east = 97, west = 68,
  frequency = "monthly"
)
```

HadEX3Geojson

*Download HadEX3 data on climate extremes for a GeoJSON region***Description**

Downloads HadEX3 data on ETCCDI climate extremes and filters the data to a geographic region. A GeoJSON polygon defines the region.

Usage

```
HadEX3Geojson(...)

hadex3_geojson(
  index,
  start_year,
  end_year,
  geojson_file,
  frequency = "annual",
  baseline = "61-90",
  output_dir = tempdir(),
  use_cache = TRUE
)
```

Arguments

...	Arguments that the aliases send to the primary function.
index	ETCCDI index name (e.g. "TXx", "Rx1day"). See list_hadex3_indices() .
start_year	Start year (1901-2018).
end_year	End year (1901-2018).
geojson_file	Path to a GeoJSON file that defines the region.

frequency	Temporal frequency: "annual" or "monthly" (default: "annual").
baseline	Reference period for the indices that use percentiles: "61-90" (default) or "81-10". This argument applies only to the annual frequency.
output_dir	Directory for temporary files (default: tempdir()).
use_cache	If TRUE, use the data in the cache (default: TRUE).

Value

A data.frame with the columns: year (and month for monthly data), latitude, longitude, value, index.

Examples

```
region <- system.file("extdata", "region.geojson", package = "varunayan")
data <- hadex3_geojson(
  index = "Tx",
  start_year = 1981, end_year = 2010,
  geojson_file = region
)
```

heatwave_days	<i>Heatwave days</i>
---------------	----------------------

Description

Flags the days of a daily maximum temperature series that fall in a heatwave, under one of three definitions:

- "imd": India Meteorological Department. A day qualifies when Tmax is at least 40 C (plains), 37 C (coastal) or 30 C (hilly) and departs at least 4.5 C from the calendar-day normal, or when Tmax is at least 45 C. Severe: departure above 6.4 C with Tmax at least 40 C (plains, coastal) or 30 C (hilly), or Tmax of at least 47 C. A heatwave needs min_duration (2) consecutive qualifying days. IMD also requires 2 stations in a meteorological sub-division; each series here is judged on its own.
- "percentile": Tmax above the calendar-day percentile of the baseline years (5-day window) for at least min_duration (3) days, as in Rohini et al. (2016) for India.
- "ehf": days covered by a three-day period with positive excess_heat_factor(); severe when EHF reaches EHF85.

Usage

```
heatwave_days(
  date,
  tmax,
  tmin = NULL,
  method = c("imd", "percentile", "ehf"),
  baseline = c(1991, 2020),
```

```

    terrain = c("plains", "coastal", "hilly"),
    percentile = 0.9,
    min_duration = NULL,
    window = 2L
  )

```

Arguments

date	Dates of a strictly increasing daily series for one location.
tmax	Daily maximum temperature (degrees Celsius).
tmin	Daily minimum temperature; required for method = "ehf".
method	"imd", "percentile" or "ehf".
baseline	Climatology years, c(first, last), contained in date.
terrain	For "imd": "plains", "coastal" or "hilly"; see <code>imd_terrain()</code> to classify a location.
percentile	Threshold quantile for "percentile".
min_duration	Minimum run of qualifying days; defaults to 2 for "imd" and 3 for "percentile" and "ehf".
window	Half-width in days of the calendar-day window.

Details

The calendar-day normal is the baseline mean over a $2 * \text{window} + 1$ day window. Percentiles use `stats::quantile()` type 8 without the in-base bootstrap of the ETCCDI indices.

Value

A data.frame with date, day (in a heatwave), severe, spell_start and spell_length (on the first day of each heatwave).

References

India Meteorological Department. Heat wave and warm night definitions. <https://mausam.imd.gov.in/pdfs/heatcolduser/Definition.pdf>

Rohini, P., Rajeevan, M. & Srivastava, A.K. (2016). On the Variability and Increasing Trends of Heat Waves over India. Scientific Reports, 6, 26153. doi:10.1038/srep26153

Examples

```

d <- seq(as.Date("2001-01-01"), as.Date("2003-12-31"), by = "day")
doy <- as.POSIXlt(d)$yday
tmax <- 33 + 8 * sin(2 * pi * (doy - 80) / 365)
tmax[d >= as.Date("2003-05-10") & d <= as.Date("2003-05-13")] <- 46
hw <- heatwave_days(d, tmax, baseline = c(2001, 2002))
subset(hw, day)

```

heat_index	<i>Calculate heat index (apparent temperature)</i>
------------	--

Description

US National Weather Service heat index: Steadman's simple formula, replaced by the Rothfus (1990) regression with its low- and high-humidity adjustments once the simple value averaged with temperature reaches 80F.

Usage

```
heat_index(temp_c, rh)
```

Arguments

temp_c	Air temperature in Celsius
rh	Relative humidity as a percentage (0-100)

Value

Heat index in Celsius

References

Rothfus, L.P. (1990). The Heat Index Equation. NWS Southern Region Technical Attachment, SR/SSD 90-23. https://www.weather.gov/media/ffc/ta_htindx.PDF

Examples

```
heat_index(35, 70)
```

heat_index_from_dewpoint	<i>Calculate heat index from dewpoint</i>
--------------------------	---

Description

Calculate heat index from dewpoint

Usage

```
heat_index_from_dewpoint(temp_c, dewpoint_c)
```

Arguments

temp_c	Air temperature in Celsius
dewpoint_c	Dewpoint temperature in Celsius

Value

Heat index in Celsius

Examples

```
heat_index_from_dewpoint(35, 25)
```

```
heat_index_risk_category
```

Heat index risk categories

Description

This function puts heat index values into heat stress risk categories. It uses the NWS categories.

Usage

```
heat_index_risk_category(hi)
```

Arguments

hi	Heat index value in Celsius
----	-----------------------------

Value

Factor with the risk category

Examples

```
heat_index_risk_category(c(27, 33, 40, 46, 55))
```

```
humidex
```

Calculate humidex (Canadian heat index)

Description

Calculate humidex (Canadian heat index)

Usage

```
humidex(temp_c, dewpoint_c)
```

Arguments

temp_c	Air temperature in Celsius
dewpoint_c	Dewpoint temperature in Celsius

Value

Humidex in Celsius

References

Masterson, J. & Richardson, F.A. (1979). Humidex, A Method of Quantifying Human Discomfort Due to Excessive Heat and Humidity. Environment Canada, Atmospheric Environment Service.

Environment and Climate Change Canada. Glossary: Humidex. https://climate.weather.gc.ca/glossary_e.html

Examples

```
humidex(30, 22)
```

IMDEXposureBbox

IMD heat exposure indicators for a bounding box

Description

Downloads IMD gridded daily maximum and minimum temperature (1 degree) for the requested years and the baseline, then computes `exposure_indicators()` for each grid cell.

Usage

```
IMDEXposureBbox(...)

imd_exposure_bbox(
  start_year,
  end_year,
  north,
  south,
  east,
  west,
  baseline = c(1991, 2020),
  ...,
  output_dir = tempdir(),
  use_cache = TRUE
)
```

Arguments

... Further arguments to `exposure_indicators()`, such as months, period, heatwave_method, terrain or hill_elevation; terrain is classified per 1 degree cell.

start_year, end_year Years to report (1951-2025).

north Latitude of the north boundary.

south	Latitude of the south boundary.
east	Longitude of the east boundary.
west	Longitude of the west boundary.
baseline	Climatology years, c(first, last), for normals and percentiles.
output_dir	Directory for the output files (default: tempdir()).
use_cache	If TRUE, use the cached data when it is available (default: TRUE).

Value

The data.frame of `exposure_indicators()` for start_year to end_year, one row per grid cell (latitude, longitude) and period.

Examples

```
jaipur <- imd_exposure_bbox(2022, 2024,
  north = 28, south = 26,
  east = 77, west = 75, months = 3:6
)
```

IMDRainfallBbox

*Download and process IMD rainfall data for a bounding box***Description**

Downloads IMD gridded rainfall data and keeps only the data in the specified bounding box.

Usage

```
IMDRainfallBbox(...)

imd_rainfall_bbox(
  request_id,
  start_year,
  end_year,
  north,
  south,
  east,
  west,
  resolution = 0.25,
  frequency = "daily",
  save_raw = FALSE,
  output_dir = tempdir(),
  use_cache = TRUE
)
```

Arguments

<code>...</code>	Arguments that the aliases send to the primary function.
<code>request_id</code>	Unique identifier for the request.
<code>start_year</code>	Start year.
<code>end_year</code>	End year.
<code>north</code>	Latitude of the north boundary.
<code>south</code>	Latitude of the south boundary.
<code>east</code>	Longitude of the east boundary.
<code>west</code>	Longitude of the west boundary.
<code>resolution</code>	Spatial resolution: 0.25 or 1.0 degrees (default: 0.25).
<code>frequency</code>	Temporal frequency: "daily", "monthly", "yearly" (default: "daily").
<code>save_raw</code>	If TRUE, keep the raw downloaded files (default: FALSE).
<code>output_dir</code>	Directory for the output files (default: <code>tempdir()</code>).
<code>use_cache</code>	If TRUE, use the cached data when it is available (default: TRUE).

Value

A data.frame with columns date, latitude, longitude and rainfall (mm), restricted to the requested region and aggregated to frequency.

Examples

```
data <- imd_rainfall_bbox(
  request_id = "maharashtra_rain",
  start_year = 2023,
  end_year = 2024,
  north = 22, south = 16,
  east = 80, west = 73,
  resolution = 0.25,
  frequency = "monthly"
)
```

IMDRainfallGeojson	<i>Download and process IMD rainfall data for a GeoJSON region</i>
--------------------	--

Description

Download and process IMD rainfall data for a GeoJSON region

Usage

```
IMDRainfallGeojson(...)  
  
imd_rainfall_geojson(  
  request_id,  
  start_year,  
  end_year,  
  geojson_file,  
  resolution = 0.25,  
  frequency = "daily",  
  save_raw = FALSE,  
  output_dir = tempdir(),  
  use_cache = TRUE  
)
```

Arguments

...	Arguments that the aliases send to the primary function.
request_id	Unique identifier for the request.
start_year	Start year (1901-2025).
end_year	End year (1901-2025).
geojson_file	Path to the GeoJSON file.
resolution	Spatial resolution: 0.25 or 1.0 degrees (default: 0.25).
frequency	Temporal frequency (default: "daily").
save_raw	If TRUE, keep the raw files (default: FALSE).
output_dir	Directory for the output files (default: tempdir()).
use_cache	If TRUE, use the cached data when it is available (default: TRUE).

Value

A data.frame with columns date, latitude, longitude and rainfall (mm), restricted to the requested region and aggregated to frequency.

Examples

```
region <- system.file("extdata", "region.geojson", package = "varunayan")  
data <- imd_rainfall_geojson(  
  request_id = "mh_rain", start_year = 2023, end_year = 2023,  
  geojson_file = region, frequency = "monthly"  
)
```

IMDRainfallPoint	<i>Download and process IMD rainfall for a single point (nearest grid cell)</i>
------------------	---

Description

Extracts the daily rainfall series for the IMD grid cell that is nearest to a (lat, lon) point. For each year, the function reads only that one cell from the disk. Thus, this function is the method with the lowest cost to get a long series for one location.

Usage

```
IMDRainfallPoint(...)

imd_rainfall_point(
  request_id,
  start_year,
  end_year,
  latitude,
  longitude,
  resolution = 0.25,
  frequency = "daily",
  save_raw = FALSE,
  output_dir = tempdir(),
  use_cache = TRUE
)
```

Arguments

...	Arguments that the aliases send to the primary function.
request_id	Unique identifier for the request.
start_year	Start year (1901-2024).
end_year	End year (1901-2024).
latitude	Latitude of the point.
longitude	Longitude of the point.
resolution	Spatial resolution: 0.25 or 1.0 degrees (default: 0.25).
frequency	Temporal frequency: "daily", "monthly", "yearly" (default: "daily").
save_raw	If TRUE, keep the raw downloaded files (default: FALSE).
output_dir	Directory for the output files (default: tempdir()).
use_cache	If TRUE, use the cached data when it is available (default: TRUE).

Value

data.frame with the rainfall series of the nearest cell.

Examples

```
powai <- tryCatch(
  imd_rainfall_point("powai", 2023, 2023, 19.1277, 72.9047,
    resolution = 1, use_cache = FALSE
  ),
  error = function(e) message("IMD server unavailable: ", conditionMessage(e))
)
```

IMDStations

IMD weather stations with coordinates

Description

Gets the India Meteorological Department (IMD) city-weather station list. As an option, it also gets the latitude and longitude of each station. The legacy IMD endpoints give only the station names. The responsive IMD site gives a JSON record for each station (`api/fetchCity_static.php`). This record contains lat and lon. The function adds these values to the station list. You can use the returned coordinates directly as input to `era5ify_point()`. You can also use them to make maps.

Usage

```
IMDStations(...)

imd_stations(
  with_coordinates = TRUE,
  cores = if (.Platform$OS.type == "windows") 1L else 2L
)
```

Arguments

<code>...</code>	Not used. This argument is necessary for compatibility with the aliases.
<code>with_coordinates</code>	Logical. If TRUE (default), the function gets latitude and longitude for each station (one request for each station). If FALSE, the function returns only station_id and name.
<code>cores</code>	Integer. The number of parallel workers that get the coordinates (the function sends this value to <code>parallel::mclapply()</code>). The default is 2 (1 on Windows, where forking is not available).

Value

A data.frame with the columns station_id and name. If with_coordinates = TRUE, the data frame also has the columns latitude and longitude. The value is NA if IMD has no coordinate for a station.

Examples

```
stations <- tryCatch(
  imd_stations(with_coordinates = FALSE),
  error = function(e) message("IMD server unavailable: ", conditionMessage(e))
)
```

IMDTemperatureBbox	<i>Download and process IMD temperature data for a bounding box</i>
--------------------	---

Description

Download and process IMD temperature data for a bounding box

Usage

```
IMDTemperatureBbox(...)

imd_temperature_bbox(
  request_id,
  start_year,
  end_year,
  north,
  south,
  east,
  west,
  var_type = "tmax",
  frequency = "daily",
  save_raw = FALSE,
  output_dir = tempdir(),
  use_cache = TRUE
)
```

Arguments

...	Arguments that the aliases send to the primary function.
request_id	Unique identifier for the request.
start_year	Start year (1951-2025).
end_year	End year (1951-2025).
north	Latitude of the north boundary.
south	Latitude of the south boundary.
east	Longitude of the east boundary.
west	Longitude of the west boundary.
var_type	Temperature type: "tmax" or "tmin".

frequency	Temporal frequency (default: "daily").
save_raw	If TRUE, keep the raw files (default: FALSE).
output_dir	Directory for the output files (default: tempdir()).
use_cache	If TRUE, use the cached data when it is available (default: TRUE).

Value

A data.frame with columns date, latitude, longitude and temperature (degrees Celsius), restricted to the requested region and aggregated to frequency.

Examples

```
data <- imd_temperature_bbox(
  request_id = "delhi_tmax",
  start_year = 2023,
  end_year = 2024,
  north = 29, south = 28,
  east = 78, west = 76,
  var_type = "tmax"
)
```

IMDTemperatureGeojson *Download and process IMD temperature data for a GeoJSON region*

Description

Download and process IMD temperature data for a GeoJSON region

Usage

```
IMDTemperatureGeojson(...)

imd_temperature_geojson(
  request_id,
  start_year,
  end_year,
  geojson_file,
  var_type = "tmax",
  frequency = "daily",
  save_raw = FALSE,
  output_dir = tempdir(),
  use_cache = TRUE
)
```

Arguments

<code>...</code>	Arguments that the aliases send to the primary function.
<code>request_id</code>	Unique identifier for the request.
<code>start_year</code>	Start year (1951-2025).
<code>end_year</code>	End year (1951-2025).
<code>geojson_file</code>	Path to the GeoJSON file.
<code>var_type</code>	Temperature type: "tmax" or "tmin".
<code>frequency</code>	Temporal frequency (default: "daily").
<code>save_raw</code>	If TRUE, keep the raw files (default: FALSE).
<code>output_dir</code>	Directory for the output files (default: <code>tempdir()</code>).
<code>use_cache</code>	If TRUE, use the cached data when it is available (default: TRUE).

Value

A data.frame with columns date, latitude, longitude and temperature (degrees Celsius), restricted to the requested region and aggregated to frequency.

Examples

```
region <- system.file("extdata", "region.geojson", package = "varunayan")
data <- imd_temperature_geojson(
  request_id = "mh_tmax", start_year = 2023, end_year = 2023,
  geojson_file = region, var_type = "tmax", frequency = "monthly"
)
```

```
imd_temperature_by_region
```

*Download IMD temperature aggregated for each GeoJSON feature
(region x time)*

Description

`imd_temperature_geojson()` returns the grid points in the GeoJSON boundary. This function is different. It returns one row for each feature (for example, each state) and each time period. Each row contains the mean temperature of the region.

Usage

```
imd_temperature_by_region(
  request_id,
  start_year,
  end_year,
  geojson_file,
```

```
feature_col = NULL,  
var_type = "tmean",  
frequency = "monthly",  
use_cache = TRUE  
)
```

Arguments

request_id	Unique identifier for the request.
start_year	Start year (≥ 1951).
end_year	End year (≤ 2024).
geojson_file	Path to a GeoJSON file. Each feature in the file is one region.
feature_col	Name of the GeoJSON property that sets the groups (for example, "state_name"). If NULL, the function uses the first column that is not the geometry column.
var_type	"tmax", "tmin", or "tmean" (mean of tmax and tmin). The default is "tmean".
frequency	"monthly" (default), "yearly", or "daily".
use_cache	If TRUE, use the cached IMD downloads when they are available (default TRUE).

Value

A data.frame with the columns region, year, month (only for monthly data), and temperature.

Examples

```
temp <- tryCatch(  
  imd_temperature_by_region(  
    request_id = "demo_region",  
    start_year = 2023, end_year = 2023,  
    geojson_file = system.file("extdata", "region.geojson", package = "varunayan"),  
    var_type = "tmax", frequency = "monthly", use_cache = FALSE  
  ),  
  error = function(e) message("IMD server unavailable: ", conditionMessage(e))  
)
```

imd_terrain	<i>IMD heatwave terrain class of a location</i>
-------------	---

Description

Classifies locations as "hilly", "coastal" or "plains" for the IMD heatwave definition in [heatwave_days\(\)](#). IMD sets the Tmax floor by terrain but does not define it. A location is hilly when it lies in Jammu and Kashmir, Ladakh, Himachal Pradesh or Uttarakhand, whose sub-divisions IMD treats as hilly down to the Jammu plains, or when its [india_elevation\(\)](#) reaches hill_elevation, the 1200 m boundary of the mid-hill regions by default. Otherwise it is coastal when land and open sea both lie within about 9 km.

Usage

```
imd_terrain(latitude, longitude, hill_elevation = 1200, cell_size = NULL)
```

Arguments

`latitude, longitude` Coordinates in decimal degrees.

`hill_elevation` Elevation (m) at or above which a location is hilly.

`cell_size` Grid spacing in degrees when the coordinates are cell centres, such as 1 for the IMD temperature grid; NULL for points.

Details

For gridded data set `cell_size` to classify whole cells from their Indian land: a cell is hilly when most of it lies in those states or its median elevation reaches `hill_elevation`, and coastal when any of it is.

Value

A character vector of "hilly", "coastal" or "plains", NA outside the grid or over sea.

References

NOAA National Centers for Environmental Information (2022). ETOPO 2022 15 Arc-Second Global Relief Model. doi:10.25921/fd45gt74

Ministry of Panchayati Raj. Local Government Directory district boundaries, via <https://bharatviz.org>.

See Also

[heatwave_days\(\)](#), [exposure_indicators\(\)](#)

Examples

```
# Shimla, Jammu, Delhi, Chennai
imd_terrain(c(31.10, 32.73, 28.61, 13.08), c(77.17, 74.86, 77.21, 80.27))
# IMD 1 degree cells holding Jammu and Rajkot
imd_terrain(c(32.5, 22.5), c(74.5, 70.5), cell_size = 1)
```

india_elevation	<i>Elevation of locations in India</i>
-----------------	--

Description

Looks up surface elevation from a 5 arc-minute (about 9 km) grid bundled with the package, covering 6-38 N and 66-98 E. Each value is the median land elevation of the 5 arc-minute cell holding the location, built by `data-raw/ind_terrain.R` from ETOPO 2022 at 60 arc-seconds.

Usage

```
india_elevation(latitude, longitude)
```

Arguments

latitude, longitude
Coordinates in decimal degrees.

Value

Elevation in metres, NA over open sea or outside the grid.

References

NOAA National Centers for Environmental Information (2022). ETOPO 2022 15 Arc-Second Global Relief Model. [doi:10.25921/fd45gt74](https://doi.org/10.25921/fd45gt74)

See Also

[imd_terrain\(\)](#)

Examples

```
# Shimla, Delhi, Leh
india_elevation(c(31.10, 28.61, 34.16), c(77.17, 77.21, 77.58))
```

is_max_var	<i>Find if a variable uses maximum aggregation</i>
------------	--

Description

Find if a variable uses maximum aggregation

Usage

```
is_max_var(var_name)
```

Arguments

var_name Variable name as a character string

Value

Logical. TRUE if the variable uses maximum aggregation

Examples

```
is_max_var("2m_temperature")
```

is_min_var	<i>Find if a variable uses minimum aggregation</i>
------------	--

Description

Find if a variable uses minimum aggregation

Usage

```
is_min_var(var_name)
```

Arguments

var_name Variable name as a character string

Value

Logical. TRUE if the variable uses minimum aggregation

Examples

```
is_min_var("2m_temperature")
```

is_rate_var	<i>Find if a variable is a rate variable</i>
-------------	--

Description

Find if a variable is a rate variable

Usage

```
is_rate_var(var_name)
```

Arguments

var_name	Variable name as a character string
----------	-------------------------------------

Value

Logical. TRUE if the variable is a rate

Examples

```
is_rate_var("2m_temperature")
```

is_sum_var	<i>Find if a variable uses sum aggregation</i>
------------	--

Description

Find if a variable uses sum aggregation

Usage

```
is_sum_var(var_name)
```

Arguments

var_name	Variable name as a character string
----------	-------------------------------------

Value

Logical. TRUE if the variable uses sum aggregation

Examples

```
is_sum_var("total_precipitation")
```

<code>is_valid_geojson</code>	<i>Find if data is valid GeoJSON</i>
-------------------------------	--------------------------------------

Description

Find if data is valid GeoJSON

Usage

```
is_valid_geojson(data)
```

Arguments

<code>data</code>	List or data structure to examine
-------------------	-----------------------------------

Value

Logical. TRUE if the data is valid GeoJSON

<code>ListAvailableVariables</code>	<i>List all available variables for a dataset type</i>
-------------------------------------	--

Description

List all available variables for a dataset type

Usage

```
ListAvailableVariables(...)
list_available_variables(dataset_type = "all")
```

Arguments

<code>...</code>	Arguments that the aliases send to the primary function.
<code>dataset_type</code>	Character string that gives the dataset type

Value

Character vector of variable names

Examples

```
head(list_available_variables("single"))
```

ListCRUTSVariables	<i>Variable data dictionary for CRU TS</i>
--------------------	--

Description

Gives the common names, units, and ERA5 equivalents of the CRU TS variable codes.

Usage

```
ListCRUTSVariables(...)
```

```
list_cru_ts_variables(...)
```

Arguments

... Arguments that the aliases send to the primary function.

Value

A data.frame with the columns: variable, name, description, unit, era5_equivalent, hadex3_equivalent.

Examples

```
list_cru_ts_variables()
```

ListHadEX3Indices	<i>List the available HadEX3 ETCCDI indices</i>
-------------------	---

Description

Returns a data.frame that describes all the ETCCDI indices of climate extremes in the HadEX3 dataset. The data.frame shows the temporal availability and the physical quantity of each index.

Usage

```
ListHadEX3Indices(...)
```

```
list_hadex3_indices(frequency = "all")
```

Arguments

... Arguments that the aliases send to the primary function.

frequency Filter by frequency: "annual", "monthly", or "all" (default).

Value

A data.frame with the columns: index, category, description, unit, annual, monthly.

Examples

```
list_hadex3_indices()
list_hadex3_indices(frequency = "monthly")
```

list_cache	List cached files
------------	-------------------

Description

List cached files

Usage

```
list_cache(source = NULL)
```

Arguments

source Filter by source: "era5", "imd", "cru_ts", "hadex3", or NULL for all

Value

A data.frame with columns file, source, size_mb and modified, one row per cached file; zero rows if the cache is empty.

Examples

```
list_cache()
```

list_imd_datasets	List available IMD datasets
-------------------	-----------------------------

Description

List available IMD datasets

Usage

```
list_imd_datasets()
```

Value

data.frame with the available IMD datasets and their properties.

Examples

```
list_imd_datasets()
```

load_india_boundaries	<i>Load India state or district boundaries</i>
-----------------------	--

Description

Downloads the India LGD boundaries from geo.bharatviz.org once and keeps them in the package cache.

Usage

```
load_india_boundaries(level = c("state", "district"))
```

Arguments

level	"state" or "district"
-------	-----------------------

Value

sf object (CRS 4326) with state_name (and district_name for districts)

Examples

```
states <- load_india_boundaries("state")
```

max_vars	<i>Variables for maximum aggregation</i>
----------	--

Description

Variables for maximum aggregation

Usage

```
max_vars
```

Value

A character vector of variable names.

Examples

```
head(max_vars)
```

`mean_radiant_temperature`*Estimate mean radiant temperature*

Description

This function estimates the mean radiant temperature (Tmrt) from meteorological variables. If full radiation data is not available, the function uses a simplified method.

Usage

```
mean_radiant_temperature(temp_c, solar_radiation = NULL, wind_speed = NULL)
```

Arguments

<code>temp_c</code>	Air temperature in Celsius
<code>solar_radiation</code>	Solar radiation in W/m2 (optional)
<code>wind_speed</code>	Wind speed in m/s (optional)

Value

Mean radiant temperature in Celsius

Examples

```
mean_radiant_temperature(30, solar_radiation = 800, wind_speed = 2)
```

`min_vars`*Variables for minimum aggregation*

Description

Variables for minimum aggregation

Usage

```
min_vars
```

Value

A character vector of variable names.

Examples

```
head(min_vars)
```

ndbi	<i>Normalized Difference Built-up Index</i>
------	---

Description

NDBI = (SWIR - NIR) / (SWIR + NIR) from surface reflectance, using the 1.55-1.75 um shortwave infrared band, e.g. Landsat 8-9 bands 6 and 5, Sentinel-2 bands 11 and 8, or Landsat 5 TM bands 5 and 4 as in Zha et al. (2003). Positive values indicate built-up or bare surfaces. Works on numeric vectors and on terra::SpatRaster layers.

Usage

```
ndbi(swir, nir)
```

Arguments

swir	Shortwave infrared reflectance.
nir	Near-infrared reflectance.

Value

NDBI in the range -1 to 1, the same shape as the inputs.

References

Zha, Y., Gao, J. & Ni, S. (2003). Use of normalized difference built-up index in automatically mapping urban areas from TM imagery. International Journal of Remote Sensing, 24(3), 583-594.
[doi:10.1080/01431160304987](https://doi.org/10.1080/01431160304987)

See Also

[ndvi\(\)](#)

Examples

```
ndbi(swir = 0.30, nir = 0.22)
```

ndvi	<i>Normalized Difference Vegetation Index</i>
------	---

Description

NDVI = (NIR - Red) / (NIR + Red) from surface reflectance, e.g. Landsat 8-9 bands 5 and 4, Sentinel-2 bands 8 and 4, or MODIS bands 2 and 1. Works on numeric vectors and on `terra::SpatRaster` layers.

Usage

```
ndvi(nir, red)
```

Arguments

nir	Near-infrared reflectance.
red	Red reflectance.

Value

NDVI in the range -1 to 1, the same shape as the inputs.

References

Tucker, C.J. (1979). Red and photographic infrared linear combinations for monitoring vegetation. *Remote Sensing of Environment*, 8(2), 127-150. doi:[10.1016/00344257\(79\)900130](https://doi.org/10.1016/00344257(79)900130)

See Also

[ndbi\(\)](#)

Examples

```
ndvi(nir = 0.45, red = 0.08)
```

parse_date_flexible	<i>Parse a date string in different formats</i>
---------------------	---

Description

Parse a date string in different formats

Usage

```
parse_date_flexible(date_string)
```

Arguments

date_string Character string in one of different date formats

Value

Date object

peak_month	<i>Month of the largest long-term mean</i>
------------	--

Description

Month of the largest long-term mean

Usage

```
peak_month(data, value, by = c("latitude", "longitude"))
```

Arguments

data Data frame with month and the by columns

value Name of the column to use, for example monthly precipitation

by Group columns. The default is each grid point.

Value

Data frame with the by columns, peak_month (1-12), peak_value and annual_total (sum of the 12 monthly means). When two months have the same mean, the first month is the peak.

Examples

```
df <- data.frame(latitude = 10, longitude = 70, month = 1:12, tp = c(1:6, 12:7))
peak_month(df, "tp")
```

plot_bars	<i>Bar chart coloured by value</i>
-----------	------------------------------------

Description

Bar chart coloured by value

Usage

```
plot_bars(  
  data,  
  x,  
  y,  
  horizontal = FALSE,  
  sort = FALSE,  
  cmap = "RdBu",  
  title = NULL  
)
```

Arguments

data	Data frame with the two columns
x	Category column (for example state_name or year)
y	Value column
horizontal	Draw horizontal bars (for long category names)
sort	Sort the bars by value, largest first
cmap	Diverging palette name from <code>ggplot2::scale_fill_distiller()</code> . The scale is centred on zero when there are negative values.
title	Plot title

Value

ggplot object

Examples

```
df <- data.frame(year = 2001:2010, dev = seq(-1, 1, length.out = 10))  
plot_bars(df, "year", "dev")
```

plot_ccf	<i>Stem plot of a cross-correlation</i>
----------	---

Description

Stem plot of a cross-correlation

Usage

```
plot_ccf(ccf, title = NULL)
```

Arguments

ccf	Data frame with lag and r, from <code>cross_correlation()</code>
title	Plot title

Value

ggplot object

Examples

```
plot_ccf(cross_correlation(sin(1:48 / 2), cos(1:48 / 2), max_lag = 6))
```

plot_dual_axis	<i>Two series on a left and a right axis</i>
----------------	--

Description

Two series on a left and a right axis

Usage

```
plot_dual_axis(data, x, left, right, log_right = FALSE, title = NULL)
```

Arguments

data	Data frame with the three columns
x	Column for the horizontal axis, for example date
left	Column for the left axis
right	Column for the right axis
log_right	Show $\log(1 + \text{right})$ on the right axis
title	Plot title

Value

ggplot object

Examples

```
df <- data.frame(month = 1:24, rain = abs(sin(1:24 / 2)) * 300, searches = abs(sin(1:24 / 2)) * 80)
plot_dual_axis(df, "month", "rain", "searches")
```

plot_heatmap

Heat map of a matrix or of a long data frame

Description

Heat map of a matrix or of a long data frame

Usage

```
plot_heatmap(
  data,
  x = NULL,
  y = NULL,
  value = NULL,
  annotate = FALSE,
  cmap = "RdYlBu",
  title = NULL
)
```

Arguments

data	Long data frame (with x, y and value), or a matrix / wide data frame such as <code>cor(df)</code> (then leave x, y and value empty)
x	Column for the columns of the heat map (month shows names)
y	Column for the rows
value	Column for the colour
annotate	Write the value in each cell
cmap	Diverging palette name from <code>ggplot2::scale_fill_distiller()</code>
title	Plot title

Value

ggplot object

Examples

```
plot_heatmap(cor(mtcars[, 1:4]), annotate = TRUE)
```

plot_map

*Map one or more columns of gridded or polygon data***Description**

An sf object with polygons gives a choropleth. A data frame with latitude and longitude gives one square for each grid point.

Usage

```
plot_map(
  data,
  column,
  boundaries = NULL,
  facet = NULL,
  log = FALSE,
  months = FALSE,
  labels = NULL,
  cmap = "viridis",
  center = NULL,
  title = NULL,
  legend_title = NULL
)
```

Arguments

data	sf object with polygons, or data frame with latitude and longitude
column	Column to colour by. A vector gives one panel per column, with one shared colour scale.
boundaries	Optional sf polygons to draw as outlines on top
facet	Optional column. One panel per value (for example a period).
log	Use a log colour scale (values must be positive)
months	The values are months (1-12). Use 12 discrete colours and month names in the legend, for example for peak_month.
labels	Optional column to write at each polygon centre
cmap	Viridis option name ("viridis", "plasma", ...) or a diverging palette name from ggplot2::scale_fill_distiller()
center	Centre a diverging palette on this value, with limits the same distance on each side (for example 0 for a bias). Use it with a diverging cmap such as "RdBu".
title	Plot title
legend_title	Legend title. The default is the column name.

Value

ggplot object

Examples

```
grid <- expand.grid(latitude = seq(10, 12, 0.5), longitude = seq(70, 72, 0.5))
grid$t2m <- grid$latitude + grid$longitude
plot_map(grid, "t2m")
```

plot_scatter	<i>Scatter plot with the 1:1 line, r and bias</i>
--------------	---

Description

Scatter plot with the 1:1 line, r and bias

Usage

```
plot_scatter(data, x, y, title = NULL)
```

Arguments

data	Data frame with the two columns
x	Column for the horizontal axis (the reference)
y	Column for the vertical axis
title	Plot title

Value

ggplot object

Examples

```
df <- data.frame(cru = 1:20, era5 = 1:20 + rnorm(20))
plot_scatter(df, "cru", "era5")
```

plot_series	<i>Line plot, one line per group</i>
-------------	--------------------------------------

Description

When x is "month", the axis shows month names.

Usage

```
plot_series(
  data,
  x,
  y,
  by = NULL,
  facet = NULL,
  smooth = NULL,
  span = 2/3,
  ribbon = NULL,
  title = NULL,
  ylabel = NULL
)
```

Arguments

data	Long data frame
x	Column for the horizontal axis (for example date or year)
y	Column for the vertical axis
by	Optional column. One line (and colour) per value.
facet	Optional column. One panel per value.
smooth	"lowess" or "linear" adds a trend line. The data line is then light grey when there is no by column.
span	Fraction of the points in each LOWESS window (stats::lowess() f)
ribbon	Optional c(low, high) columns to shade, for example c("temperature_min", "temperature_max")
title	Plot title
ylabel	Vertical axis label. The default is y.

Value

ggplot object

Examples

```
df <- data.frame(year = 2001:2020, t2m = 25 + 0.03 * (1:20) + rnorm(20, sd = 0.2))
plot_series(df, "year", "t2m", smooth = "linear")
```

PopulateSampleCache	<i>Fill the cache with sample IMD data</i>
---------------------	--

Description

Copies sample IMD data files to the cache for offline tests.

Usage

```
PopulateSampleCache(...)
```

```
populate_sample_cache(force = FALSE)
```

Arguments

...	Arguments for the main function (for use by aliases).
force	If TRUE, overwrite the cached files that exist (default: FALSE)

Value

Invisibly, a named list of paths to the cached sample files, or NULL if no sample directory exists.

Examples

```
populate_sample_cache()
```

print_timing_summary	<i>Print a summary of the time data</i>
----------------------	---

Description

Print a summary of the time data

Usage

```
print_timing_summary()
```

Value

The timing data frame from [get_timings\(\)](#), invisibly (NULL if empty).

Examples

```
print_timing_summary()
```

process_imd_files	<i>Process multiple IMD files</i>
-------------------	-----------------------------------

Description

Reads and combines multiple IMD data files.

Usage

```
process_imd_files(  
  file_paths,  
  var_type,  
  resolution = NULL,  
  years = NULL,  
  bbox = NULL  
)
```

Arguments

file_paths	Character vector of file paths.
var_type	Variable type: "rain", "tmax", or "tmin".
resolution	Resolution (for rainfall): 0.25 or 1.0.
years	Integer vector. The year of each file.
bbox	Optional named list or vector (north, south, east, west). The function sends it to the rainfall reader, which crops the grid at read time. If NULL, the function reads the full grid (default).

Value

A data.frame with columns date, latitude, longitude and the value column (rainfall or temperature), combining all files.

Examples

```
files <- download_imd_temperature(2023, 2024, var_type = "tmax")  
data <- process_imd_files(files, "tmax", years = c(2023, 2024))
```

```
process_netcdf_to_dataframe
```

Extract data from a NetCDF file into a data.frame

Description

This function uses ncdf4 to read the file quickly. If ncdf4 fails, it uses stars.

Usage

```
process_netcdf_to_dataframe(netcdf_file)
```

Arguments

netcdf_file Path to the NetCDF file, as a character string

Value

data.frame with processed climate data

```
rate_vars
```

Rate variables to average

Description

Rate variables to average

Usage

```
rate_vars
```

Value

A character vector of variable names.

Examples

```
head(rate_vars)
```

read_cdsapirc	<i>Read CDS API credentials from ~/.cdsapirc file</i>
---------------	---

Description

Read CDS API credentials from ~/.cdsapirc file

Usage

```
read_cdsapirc(file_path = "~/cdsapirc")
```

Arguments

file_path	Path to .cdsapirc file (default: "~/cdsapirc")
-----------	--

Value

A named list of the fields in the file (typically url and key), or NULL if the file does not exist or cannot be parsed.

Examples

```
f <- tempfile()
writeLines(c("url: https://cds.climate.copernicus.eu/api", "key: abc-123"), f)
read_cdsapirc(f)
```

read_imd_rainfall	<i>Read IMD NetCDF rainfall file</i>
-------------------	--------------------------------------

Description

Reads IMD NetCDF rainfall data and converts the data to a data.frame.

Usage

```
read_imd_rainfall(file_path, resolution, year, bbox = NULL)
```

Arguments

file_path	Path to the IMD NetCDF file (.nc).
resolution	Spatial resolution: 0.25 or 1.0.
year	Year of the data.
bbox	Optional named list or vector (north, south, east, west). If you set it, the function reads only that spatial slab from the disk (fast path). If NULL, the function reads the full grid.

Value

data.frame with columns: date, latitude, longitude, rainfall

Examples

```
f <- download_imd_rainfall(2023, 2023, resolution = 0.25)
rain_data <- read_imd_rainfall(f, 0.25, 2023)
```

read_imd_temperature	<i>Read IMD binary temperature file</i>
----------------------	---

Description

Reads IMD binary temperature data (maximum or minimum) and converts the data to a data.frame.

Usage

```
read_imd_temperature(file_path, var_type, year)
```

Arguments

file_path	Path to the IMD binary file (.grd).
var_type	Variable type: "tmax" or "tmin".
year	Year of the data.

Value

data.frame with columns: date, latitude, longitude, temperature

Examples

```
f <- download_imd_temperature(2023, 2023, var_type = "tmax")
tmax_data <- read_imd_temperature(f, "tmax", 2023)
```

regrid	<i>Average onto a coarser regular grid</i>
--------	--

Description

Each point goes into the cell of size `resolution` that contains it. The result has the cell centres, so a 0.5 degree grid has centres at x.25 and x.75, the same as CRU TS.

Usage

```
regrid(  
  data,  
  value,  
  resolution,  
  by = NULL,  
  lat_col = "latitude",  
  lon_col = "longitude"  
)
```

Arguments

<code>data</code>	Data frame with latitude and longitude columns
<code>value</code>	Name of the column to average
<code>resolution</code>	Target cell size in degrees
<code>by</code>	Optional extra group columns, for example "year"
<code>lat_col</code>	Name of the latitude column
<code>lon_col</code>	Name of the longitude column

Value

Data frame with `lat_col`, `lon_col`, the `by` columns and `value`

Examples

```
df <- expand.grid(latitude = seq(10, 10.75, 0.25), longitude = seq(70, 70.75, 0.25))  
df$t2m <- seq_len(nrow(df))  
regrid(df, "t2m", resolution = 0.5)
```

relative_humidity_from_dewpoint

Calculate relative humidity from temperature and dewpoint

Description

This function uses the Magnus-Tetens approximation to calculate the relative humidity from the air temperature and the dewpoint temperature.

Usage

```
relative_humidity_from_dewpoint(temp_c, dewpoint_c)
```

Arguments

temp_c	Air temperature in Celsius
dewpoint_c	Dewpoint temperature in Celsius

Value

Relative humidity as a percentage (0-100)

Examples

```
relative_humidity_from_dewpoint(25, 18)
```

SearchVariable

Search for ERA5 variables by keyword

Description

Search for ERA5 variables by keyword

Usage

```
SearchVariable(...)
```

```
search_variable(keyword, dataset_type = "all", exact_match = FALSE)
```

Arguments

...	Arguments that the aliases send to the primary function.
keyword	Character string to find in variable names and descriptions
dataset_type	Character string that gives the dataset type ("single", "pressure", or "all")
exact_match	Logical. If TRUE, use an exact match

Value

A data.frame with columns variable_name, description, units, dataset_type and category, one row per matching variable.

Examples

```
# Search for temperature variables
temp_vars <- search_variable("temperature")

# Search only in pressure level data
pressure_temp <- search_variable("temperature", dataset_type = "pressure")
```

seasonal_cycle	<i>Mean for each calendar month</i>
----------------	-------------------------------------

Description

Mean for each calendar month

Usage

```
seasonal_cycle(data, value, by = NULL)
```

Arguments

- data Data frame with a month column (1-12)
- value Name of the column to average
- by Optional group columns, for example "country"

Value

Data frame with the by columns, month and value

Examples

```
df <- data.frame(month = rep(1:12, 2), t2m = c(1:12, 3:14))
seasonal_cycle(df, "t2m")
```

seasonal_stat	<i>Seasonal total or mean, averaged over years</i>
---------------	--

Description

For each group and year, the function takes the sum or mean of the selected months. Then it calculates the mean over the years.

Usage

```
seasonal_stat(  
  data,  
  value,  
  months,  
  how = c("sum", "mean"),  
  by = c("latitude", "longitude")  
)
```

Arguments

data	Data frame with year, month (or date) and the by columns
value	Name of the column to use
months	Months of the season, for example 6:8
how	"sum" (seasonal total) or "mean"
by	Group columns. The default is each grid point.

Value

Data frame with the by columns and value

Examples

```
df <- expand.grid(latitude = 10, longitude = 70, year = 2001:2002, month = 1:12)  
df$tp <- seq_len(nrow(df))  
seasonal_stat(df, "tp", months = 6:8)
```

SetupCdsCredentials	<i>Configure CDS credentials for ERA5 data access</i>
---------------------	---

Description

This function configures the Copernicus Climate Data Store (CDS) credentials for ERA5 downloads. The function examines the credentials in this order:

1. The key argument that you give directly
2. CDS_API_KEY environment variable
3. ~/.cdsapirc file

Usage

```
SetupCdsCredentials(...)
```

```
setup_cds_credentials(key = NULL)
```

Arguments

...	Arguments passed to the main function (used by aliases).
key	Your CDS API key (UUID format). If NULL, the function tries to read the key from the CDS_API_KEY environment variable or the ~/.cdsapirc file.

Value

Invisibly, TRUE once the key has been registered with 'ecmwf'. Errors if no key can be found.

Examples

```
setup_cds_credentials()
```

ShowCacheInfo	<i>Show cache contents and statistics</i>
---------------	---

Description

Show cache contents and statistics

Usage

```
ShowCacheInfo(...)
```

```
show_cache_info()
```

Arguments

... Arguments for the main function (for use by aliases).

Value

Invisibly, a data.frame with columns name, size_mb and mtime describing cached files, or NULL if the cache is empty. Called mainly for its side effect of printing a summary as messages.

Examples

```
show_cache_info()
```

spatial_mean	<i>Spatial mean over grid points</i>
--------------	--------------------------------------

Description

Spatial mean over grid points

Usage

```
spatial_mean(  
  data,  
  value,  
  by = c("year", "month"),  
  weight = "coslat",  
  lat_col = "latitude"  
)
```

Arguments

data	Long data frame with a latitude column and the by columns
value	Name of the column to average
by	Group columns, for example c("year", "month") or "year"
weight	"coslat" weights each point by cos(latitude), so that points near the poles count less. NULL gives a plain mean.
lat_col	Name of the latitude column

Value

Data frame with the by columns and value. A date column is added when by holds year and month.

Examples

```
grid <- expand.grid(latitude = c(10, 20), longitude = 70, year = 2000, month = 1:2)  
grid$t2m <- c(20, 30, 21, 31)  
spatial_mean(grid, "t2m")
```

sum_vars	<i>Variables to sum over time</i>
----------	-----------------------------------

Description

Accumulation variables (precipitation, radiation). Temporal aggregation uses the sum for these variables.

Usage

```
sum_vars
```

Value

A character vector of variable names.

Examples

```
head(sum_vars)
```

time_operation	<i>Measure the time of an operation and record the duration</i>
----------------	---

Description

Measure the time of an operation and record the duration

Usage

```
time_operation(expr, label, verbose = TRUE)
```

Arguments

expr	Expression to measure
label	Label for the operation
verbose	If TRUE, print the time information (default: TRUE)

Value

The value of expr. The elapsed time is recorded and can be retrieved with [get_timings\(\)](#).

Examples

```
x <- time_operation(sum(1:10), "sum")
get_timings()
```

utci	<i>Calculate UTCI (Universal Thermal Climate Index)</i>
------	---

Description

This function uses the polynomial approximation of Bröde et al. (2012) to calculate UTCI. The approximation uses a multi-node model of human thermoregulation.

Usage

```
utci(temp_c, wind_speed, dewpoint_c, tmrt = NULL)
```

Arguments

temp_c	Air temperature in Celsius (-50 to 50)
wind_speed	Wind speed at 10m height in m/s (0.5 to 17)
dewpoint_c	Dewpoint temperature in Celsius (to calculate vapor pressure)
tmrt	Mean radiant temperature in Celsius (optional, the default is temp_c)

Value

UTCI in Celsius

References

Bröde, P., et al. (2012). Deriving the operational procedure for the Universal Thermal Climate Index (UTCI). International Journal of Biometeorology, 56(3), 481-494. doi:[10.1007/s0048401104541](https://doi.org/10.1007/s0048401104541)

Examples

```
utci(30, wind_speed = 2, dewpoint_c = 20)
utci(35, wind_speed = 1, dewpoint_c = 25, tmrt = 45)
```

utci_category	<i>UTCI thermal stress categories</i>
---------------	---------------------------------------

Description

This function puts UTCI values into thermal stress categories.

Usage

```
utci_category(utci_val)
```

Arguments

utci_val UTCI value in Celsius

Value

Factor with the thermal stress category

Examples

```
utci_category(c(-20, 0, 20, 30, 40))
```

utci_sparse	<i>Calculate UTCI with a sparse regression approximation</i>
-------------	--

Description

This function uses the sparse regression approximation of Roman et al. (2025) to calculate UTCI. This approximation uses Legendre polynomials. It is more accurate than the original polynomial of Bröde et al. (2012). It has fewer terms and better numerical stability.

Usage

```
utci_sparse(temp_c, tmrt, wind_speed, rh)
```

Arguments

temp_c Air temperature in Celsius (-50 to 50)
tmrt Mean radiant temperature in Celsius
wind_speed Wind speed at 10m height in m/s (0.5 to 30.3)
rh Relative humidity as a percentage (5 to 100)

Value

UTCI in Celsius

References

Roman, S., Todorovski, L., Dzeroski, S., & Skok, G. (2025). Approximating the universal thermal climate index using sparse regression with orthogonal polynomials. [doi:10.48550/arXiv.2508.11307](https://doi.org/10.48550/arXiv.2508.11307)

Roman, S. (2025). Code for Approximating the universal thermal climate index (UTCI) using sparse regression with orthogonal polynomials. Zenodo. [doi:10.5281/zenodo.17465548](https://doi.org/10.5281/zenodo.17465548)

Examples

```
utci_sparse(30, tmrt = 40, wind_speed = 2, rh = 60)  
utci_sparse(35, tmrt = 35, wind_speed = 1, rh = 80)
```

validate_bbox	<i>Make sure that bounding box coordinates are valid</i>
---------------	--

Description

Make sure that bounding box coordinates are valid

Usage

validate_bbox(north, south, east, west)

Arguments

north	Northern boundary
south	Southern boundary
east	Eastern boundary
west	Western boundary

Value

Logical. TRUE if the bounding box is valid

validate_coordinates	<i>Make sure that geographic coordinates are valid</i>
----------------------	--

Description

Make sure that geographic coordinates are valid

Usage

validate_coordinates(lat, lon)

Arguments

lat	Latitude value
lon	Longitude value

Value

Logical. TRUE if the coordinates are valid

`validate_era5_variables`*Validate ERA5 variable names*

Description

Validate ERA5 variable names

Usage

```
validate_era5_variables(variables, dataset_type)
```

Arguments

<code>variables</code>	Character vector of variable names to validate
<code>dataset_type</code>	Character string: "single" or "pressure"

Value

Logical vector that shows which variables are valid

`vapor_pressure_from_dewpoint`*Calculate vapor pressure from dewpoint temperature*

Description

Calculate vapor pressure from dewpoint temperature

Usage

```
vapor_pressure_from_dewpoint(dewpoint_c)
```

Arguments

<code>dewpoint_c</code>	Dewpoint temperature in Celsius
-------------------------	---------------------------------

Value

Vapor pressure in hPa (hectopascals)

Examples

```
vapor_pressure_from_dewpoint(20)
```

varunayan-aliases *PascalCase Aliases*

Description

PascalCase aliases for all exported functions. The aliases keep backward compatibility.

Usage

```
ERA5ifyGeojson(...)

era5ify_geojson(
  request_id,
  variables,
  start_date,
  end_date,
  json_file,
  dataset_type = "single",
  pressure_levels = NULL,
  frequency = "hourly",
  resolution = 0.25,
  save_raw = FALSE,
  output_dir = tempdir(),
  use_cache = TRUE,
  convert_units = TRUE,
  verbose = FALSE,
  level = c("union", "feature")
)
```

Arguments

...	Arguments passed to the main function (used by aliases).
request_id	Unique identifier for the data request
variables	List of ERA5 variables to download
start_date	Start date in "YYYY-MM-DD" format
end_date	End date in "YYYY-MM-DD" format
json_file	Path to the GeoJSON file that defines the region
dataset_type	Type of dataset ("single" or "pressure")
pressure_levels	Pressure levels for pressure dataset
frequency	Temporal frequency ("hourly", "daily", "monthly")
resolution	Spatial resolution in degrees (default: 0.25)
save_raw	If TRUE, save the raw downloaded files
output_dir	Directory for the saved files (default: tempdir())

use_cache	If TRUE, use cached data when it is available (default: TRUE)
convert_units	If TRUE, convert units to user-friendly formats (default: TRUE). When TRUE, the function returns temperature variables in Celsius (converted from Kelvin). It returns precipitation variables in mm (converted from meters).
verbose	If TRUE, print detailed progress messages
level	"union" (default) returns one row for each grid cell inside the union of all the features. "feature" returns one row for each feature (for example, each district), with the mean of the cells inside it. Such rows have a feature_id column (the row number of the feature) and the feature properties in place of latitude and longitude. A feature smaller than a grid cell gets the nearest cell.

Value

data.frame with processed climate data. When convert_units = TRUE:

- Temperature variables (e.g., 2m_temperature): Celsius
- Precipitation variables (e.g., total_precipitation): mm
- Other variables: original ERA5 units

Examples

```
region <- system.file("extdata", "region.geojson", package = "varunayan")
setup_cds_credentials(key = "your-cds-api-key")

data <- era5ify_geojson(
  request_id = "my_request",
  variables = c("2m_temperature", "total_precipitation"),
  start_date = "2023-01-01",
  end_date = "2023-01-31",
  json_file = region
)
# Temperature is in Celsius. Precipitation is in mm.
```

visualize_grid_overlap

Show the overlap of grid points and polygons

Description

Show the overlap of grid points and polygons

Usage

```
visualize_grid_overlap(
  grid_data,
  polygons,
  show_centroids = TRUE,
  grid_color = "#E74C3C",
  polygon_fill = NA,
  polygon_color = "#2C3E50",
  centroid_color = "#3498DB",
  title = "Grid-Polygon Overlap"
)
```

Arguments

<code>grid_data</code>	Data frame with longitude and latitude columns, or the path to a NetCDF or CSV file
<code>polygons</code>	sf object, or the path to a GeoJSON file
<code>show_centroids</code>	Logical. If TRUE, show the polygon centroids
<code>grid_color</code>	Color for grid points
<code>polygon_fill</code>	Fill color for polygons
<code>polygon_color</code>	Border color for polygons
<code>centroid_color</code>	Color for centroids
<code>title</code>	Plot title

Value

ggplot object

Examples

```
grid <- expand.grid(longitude = seq(72.5, 77.5, by = 1), latitude = seq(18.5, 21.5, by = 1))
grid$temperature <- seq_len(nrow(grid))
cells <- sf::st_make_grid(sf::st_as_sfc(sf::st_bbox(
  c(xmin = 72, ymin = 18, xmax = 78, ymax = 22),
  crs = 4326
)), n = c(2, 1))
polys <- sf::st_sf(region = c("west", "east"), geometry = cells)
visualize_grid_overlap(grid, polys)
```

warm_nights

*Warm nights***Description**

Flags warm nights in a daily minimum temperature series:

- "imd": India Meteorological Department. Tmax of at least 40 C and Tmin departing at least 4.5 C from the calendar-day normal; very warm (flagged severe) above 6.4 C.
- "percentile": Tmin above the calendar-day percentile of the baseline years (ETCCDI TN90p with the default 0.9).
- "absolute": Tmin above threshold (ETCCDI tropical nights, TR, with the default 20 C).

Usage

```
warm_nights(
  date,
  tmin,
  tmax = NULL,
  method = c("imd", "percentile", "absolute"),
  baseline = c(1991, 2020),
  percentile = 0.9,
  threshold = 20,
  min_duration = 1L,
  window = 2L
)
```

Arguments

date	Dates of a strictly increasing daily series for one location.
tmin	Daily minimum temperature (degrees Celsius).
tmax	Daily maximum temperature; required for method = "imd".
method	"imd", "percentile" or "absolute".
baseline	Climatology years, c(first, last), contained in date.
percentile	Threshold quantile for "percentile".
threshold	Tmin threshold for "absolute" (degrees Celsius).
min_duration	Minimum run of warm nights counted as a spell.
window	Half-width in days of the calendar-day window.

Value

A data.frame with date, day (a warm night within a spell), severe, spell_start and spell_length.

References

India Meteorological Department. Heat wave and warm night definitions. <https://mausam.imd.gov.in/pdfs/heatcolduser/Definition.pdf>

Zhang, X., Alexander, L., Hegerl, G.C., Jones, P., Klein Tank, A., Peterson, T.C., Trewin, B. & Zwiers, F.W. (2011). Indices for monitoring changes in extremes based on daily temperature and precipitation data. WIREs Climate Change, 2(6), 851-870. doi:10.1002/wcc.147

Examples

```
d <- seq(as.Date("2001-01-01"), as.Date("2001-12-31"), by = "day")
tmin <- 22 + 6 * sin(2 * pi * (as.POSIXlt(d)$yday - 80) / 365)
wn <- warm_nights(d, tmin, method = "absolute", threshold = 27)
sum(wn$day)
```

wbgt	<i>Wet Bulb Globe Temperature</i>
------	-----------------------------------

Description

Computes WBGT by one of two methods:

- "simple": the Australian Bureau of Meteorology closed form $0.567 * T + 0.393 * e + 3.94$ from temperature and dewpoint only (`wbgt_simple()`). Assumes moderate sun and light wind; suited to daily data.
- "liljegren": the physical outdoor model of `wbgt_liljegren()`, which needs wind, solar radiation, time and location; suited to hourly data.

Usage

```
wbgt(temp_c, dewpoint_c, method = c("simple", "liljegren"), ...)
```

Arguments

temp_c	Air temperature (degrees Celsius).
dewpoint_c	Dewpoint temperature (degrees Celsius).
method	"simple" or "liljegren".
...	For method = "liljegren", arguments passed to <code>wbgt_liljegren()</code> : wind_speed, solar, datetime, lat, lon and optionally pressure, wind_height, urban, delta_t.

Value

A numeric vector of WBGT (degrees Celsius).

Examples

```
wbgt(38, 24)
wbgt(38, 24,
     method = "liljegren", wind_speed = 3, solar = 800,
     datetime = as.POSIXct("2024-05-20 08:30:00", tz = "UTC"),
     lat = 26.9, lon = 75.8
)
```

wbgt_from_dewpoint	<i>Calculate WBGT from dewpoint</i>
--------------------	-------------------------------------

Description

This function is an alias for `wbgt_simple()`. It calculates the BoM closed-form WBGT from temperature and dewpoint.

Usage

```
wbgt_from_dewpoint(temp_c, dewpoint_c)
```

Arguments

temp_c	Air temperature in Celsius
dewpoint_c	Dewpoint temperature in Celsius

Value

WBGT in Celsius

Examples

```
wbgt_from_dewpoint(35, 25)
```

wbgt_liljegren	<i>Outdoor Wet Bulb Globe Temperature (Liljegren method)</i>
----------------	--

Description

Physically based outdoor WBGT from standard meteorological variables, following Liljegren et al. (2008). Globe and natural wet bulb temperatures are solved iteratively from energy balances that include direct and diffuse solar radiation, so this is the sun-exposed WBGT of ISO 7243. Inputs should be instantaneous or hourly values; for ERA5, solar is the hourly accumulated surface solar radiation downwards divided by 3600 and datetime the middle of the accumulation hour.

Usage

```
wbgt_liljegren(
  temp_c,
  rh,
  wind_speed,
  solar,
  datetime,
  lat,
  lon,
  pressure = 1013.25,
  wind_height = 10,
  urban = FALSE,
  delta_t = 0,
  components = FALSE
)
```

Arguments

temp_c	Air temperature (degrees Celsius).
rh	Relative humidity (percent).
wind_speed	Wind speed (m/s) measured at wind_height.
solar	Global horizontal solar irradiance (W/m2).
datetime	POSIXct time of each observation; converted to UTC.
lat, lon	Latitude and longitude (decimal degrees).
pressure	Surface pressure (hPa).
wind_height	Height of the wind measurement (m). Values other than 2 are scaled to 2 m with a stability-dependent power law.
urban	Use the urban (TRUE) or rural (FALSE) power-law exponents.
delta_t	Vertical temperature difference, upper minus lower level (degrees Celsius); sets the night-time stability class only.
components	If TRUE, return globe, natural wet bulb and psychrometric wet bulb temperatures as well.

Details

This product includes software produced by UChicago Argonne, LLC under Contract No. DE-AC02-06CH11357 with the Department of Energy.

Value

A numeric vector of WBGT (degrees Celsius), or with components = TRUE a data.frame with columns wbgt, globe, natural_wet_bulb, wet_bulb and wind_2m. NA where the iteration does not converge.

References

Liljegren, J.C., Carhart, R.A., Lawday, P., Tschopp, S. & Sharp, R. (2008). Modeling the Wet Bulb Globe Temperature Using Standard Meteorological Measurements. *Journal of Occupational and Environmental Hygiene*, 5(10), 645-655. doi:[10.1080/15459620802310770](https://doi.org/10.1080/15459620802310770)

See Also

[wbgt\(\)](#) to choose between this and the closed-form estimate.

Examples

```
t <- as.POSIXct("2024-05-20 08:30:00", tz = "UTC") # 14:00 IST
wbgt_liljegren(42,
  rh = 25, wind_speed = 3, solar = 850,
  datetime = t, lat = 26.9, lon = 75.8
)
wbgt_liljegren(42, 25, 3, 850, t, 26.9, 75.8, components = TRUE)
```

wbgt_risk_category	<i>Heat stress risk categories</i>
--------------------	------------------------------------

Description

Classify heat stress risk using the US National Weather Service WBGT flag thresholds of 78, 82, 85 and 88 F (25.6, 27.8, 29.4 and 31.1 C).

Usage

```
wbgt_risk_category(wbgt)
```

Arguments

wbgt	WBGT value in Celsius
------	-----------------------

Value

Factor with the risk category

Examples

```
wbgt_risk_category(c(25, 28, 31, 34))
```

wbgt_shade

Calculate shade/indoor Wet Bulb Globe Temperature (ISO 7243)

Description

This function uses the indoor formula $0.7T_w + 0.3T_a$. To get a closed-form estimate from only temperature and humidity, use `wbgt_simple()`.

Usage

```
wbgt_shade(temp_c, wet_bulb_c)
```

Arguments

temp_c	Air temperature in Celsius
wet_bulb_c	Wet bulb temperature in Celsius

Value

WBGT in Celsius

Examples

```
wbgt_shade(35, 27)
```

wbgt_simple

Calculate WBGT (Wet Bulb Globe Temperature)

Description

Australian Bureau of Meteorology approximation $WBGT = 0.567 * T + 0.393 * e + 3.94$, with e the vapour pressure in hPa. It assumes moderately high solar radiation and light wind, so it overestimates WBGT in cloudy or windy conditions and at night. Use daily maximum temperature for afternoon conditions. For the physical outdoor model see [wbgt_liljegren\(\)](#).

Usage

```
wbgt_simple(temp_c, dewpoint_c)
```

Arguments

temp_c	Air temperature in Celsius
dewpoint_c	Dewpoint temperature in Celsius

Value

WBGT in Celsius

References

Australian Bureau of Meteorology. Thermal Comfort observations: About the approximation to the WBGT. https://www.bom.gov.au/info/thermal_stress/ (formula from American College of Sports Medicine (1984), Prevention of thermal injuries during distance running: position stand, Medical Journal of Australia, 141, 876).

Carter, A.W., Zaitchik, B.F., Gohlke, J.M., Wang, S., & Richardson, M.B. (2020). Methods for Estimating Wet Bulb Globe Temperature From Remote and Low-Cost Data: A Comparative Study in Central Alabama. GeoHealth, 4(5), e2019GH000231. doi:10.1029/2019GH000231

Examples

```
wbgt_simple(35, 25)
```

```
wet_bulb_from_dewpoint
```

Calculate wet bulb temperature from dewpoint

Description

Calculate wet bulb temperature from dewpoint

Usage

```
wet_bulb_from_dewpoint(temp_c, dewpoint_c)
```

Arguments

temp_c	Air temperature in Celsius
dewpoint_c	Dewpoint temperature in Celsius

Value

Wet bulb temperature in Celsius

Examples

```
wet_bulb_from_dewpoint(30, 22)
```

wet_bulb_temperature	<i>Calculate wet bulb temperature</i>
----------------------	---------------------------------------

Description

This function uses the Stull (2011) empirical formula to calculate the wet bulb temperature. The formula is applicable to temperatures between -20C and 50C and to RH between 5% and 99%.

Usage

```
wet_bulb_temperature(temp_c, rh)
```

Arguments

temp_c	Air temperature in Celsius
rh	Relative humidity as a percentage (0-100)

Value

Wet bulb temperature in Celsius

References

Stull, R. (2011). Wet-Bulb Temperature from Relative Humidity and Air Temperature. Journal of Applied Meteorology and Climatology, 50(11), 2267-2269. doi:[10.1175/JAMCD110143.1](https://doi.org/10.1175/JAMCD110143.1)

Examples

```
wet_bulb_temperature(30, 60)
```

Index

aggregate_by_frequency, [5](#)
aggregate_imd_by_frequency, [6](#)
aggregate_to_polygons, [6](#)
anomaly, [8](#)

cache_stats, [8](#)
calc_heat_indices, [9](#)
categorize_variables, [9](#)
check_grid_coverage, [10](#)
check_system_readiness
 (CheckSystemReadiness), [10](#)
CheckSystemReadiness, [10](#)
cleanup_temp_files, [11](#)
clear_cache (ClearCache), [12](#)
clear_timings, [12](#)
ClearCache, [12](#)
combine_netcdf_files, [13](#)
compare, [13](#)
compare_grids, [14](#)
convert_to_geojson, [15](#)
create_geojson_from_bbox, [15](#)
create_temp_geojson_file, [16](#)
create_temporal_chunks, [16](#)
cross_correlation, [17](#)
cross_correlation(), [85](#)
cru_ts_bbox (CRUTSBbox), [18](#)
cru_ts_geojson (CRUTSGeojson), [19](#)
CRUTSBbox, [18](#)
CRUTSGeojson, [19](#)

describe_variables (DescribeVariables),
 [20](#)
DescribeVariables, [20](#)
dewpoint_from_relative_humidity, [21](#)
download_era5_pressure, [21](#)
download_era5_single, [22](#)
download_imd_rainfall, [23](#)
download_imd_temperature, [24](#)

ecmwfr::wf_set_key(), [52](#)

ensure_output_dir, [25](#)
era5ify_bbox (ERA5ifyBbox), [25](#)
era5ify_geojson (varunayan-aliases), [106](#)
era5ify_geojson(), [38](#)
era5ify_point (ERA5ifyPoint), [27](#)
era5ify_point(), [67](#)
ERA5ifyBbox, [25](#)
ERA5ifyGeojson (varunayan-aliases), [106](#)
ERA5ifyPoint, [27](#)
excess_heat_factor, [29](#)
excess_heat_factor(), [58](#)
exclude_cols, [30](#)
exposure_indicators, [30](#)
exposure_indicators(), [62](#), [63](#), [72](#)
extract_point_data, [32](#)

filter_dataframe_by_geojson, [33](#)
filter_imd_by_bbox, [33](#)
filter_imd_by_geojson, [34](#)
filter_netcdf_by_bbox, [35](#)
filter_netcdf_by_geojson, [35](#)
format_date_range, [36](#)
format_pressure_levels, [36](#)

get_available_datasets, [51](#)
get_available_pressure_levels
 (GetAvailablePressureLevels),
 [37](#)
get_bbox_from_sf, [52](#)
get_cache_dir (GetCacheDir), [37](#)
get_cds_credentials, [52](#)
get_era5_country_temperature
 (GetERA5CountryTemperature), [38](#)
get_era5_daily_climate
 (GetERA5DailyClimate), [39](#)
get_era5_daily_heat_data
 (GetERA5DailyHeatIndexData), [41](#)
get_era5_daily_heat_index_data
 (GetERA5DailyHeatIndexData), [41](#)

- get_era5_daily_humidity
(GetERA5DailyHumidity), 43
- get_era5_daily_temperature
(GetERA5DailyTemperature), 44
- get_era5_daily_wet_bulb
(GetERA5DailyWetBulb), 46
- get_era5_daily_wind (GetERA5DailyWind), 47
- get_era5_monthly_heat_data
(GetERA5MonthlyHeatIndexData), 49
- get_era5_monthly_heat_index_data
(GetERA5MonthlyHeatIndexData), 49
- get_imd_grid_specs, 53
- get_package_info (GetPackageInfo), 51
- get_pressure_level_variable_names, 54
- get_pressure_level_variables, 53
- get_single_level_variable_names, 54
- get_single_level_variables, 54
- get_time_values, 55
- get_timings, 55
- get_timings(), 90, 101
- GetAvailablePressureLevels, 37
- GetCacheDir, 37
- GetERA5CountryTemperature, 38
- GetERA5DailyClimate, 39
- GetERA5DailyHeatData
(GetERA5DailyHeatIndexData), 41
- GetERA5DailyHeatIndexData, 41
- GetERA5DailyHumidity, 43
- GetERA5DailyTemperature, 44
- GetERA5DailyWetBulb, 46
- GetERA5DailyWind, 47
- GetERA5MonthlyHeatData
(GetERA5MonthlyHeatIndexData), 49
- GetERA5MonthlyHeatIndexData, 49
- GetPackageInfo, 51
- ggplot2::scale_fill_distiller(), 84, 86, 87
- hadex3_bbox (HadEX3Bbox), 56
- hadex3_geojson (HadEX3Geojson), 57
- HadEX3Bbox, 56
- HadEX3Geojson, 57
- heat_index, 60
- heat_index_from_dewpoint, 60
- heat_index_risk_category, 61
- heatwave_days, 58
- heatwave_days(), 31, 71, 72
- humidex, 61
- imd_exposure_bbox (IMDExposureBbox), 62
- imd_exposure_bbox(), 32
- imd_rainfall_bbox (IMDRainfallBbox), 63
- imd_rainfall_geojson
(IMDRainfallGeojson), 64
- imd_rainfall_point (IMDRainfallPoint), 66
- imd_stations (IMDStations), 67
- imd_temperature_bbox
(IMDTemperatureBbox), 68
- imd_temperature_by_region, 70
- imd_temperature_geojson
(IMDTemperatureGeojson), 69
- imd_temperature_geojson(), 70
- imd_terrain, 71
- imd_terrain(), 31, 59, 73
- IMDExposureBbox, 62
- IMDRainfallBbox, 63
- IMDRainfallGeojson, 64
- IMDRainfallPoint, 66
- IMDStations, 67
- IMDTemperatureBbox, 68
- IMDTemperatureGeojson, 69
- india_elevation, 73
- india_elevation(), 71
- is_max_var, 73
- is_min_var, 74
- is_rate_var, 75
- is_sum_var, 75
- is_valid_geojson, 76
- list_available_variables
(ListAvailableVariables), 76
- list_cache, 78
- list_cru_ts_variables
(ListCRUTSVariables), 77
- list_cru_ts_variables(), 18, 19
- list_hadex3_indices
(ListHadEX3Indices), 77
- list_hadex3_indices(), 56, 57
- list_imd_datasets, 78
- ListAvailableVariables, 76
- ListCRUTSVariables, 77
- ListHadEX3Indices, 77
- load_india_boundaries, 79

max_vars, 79
mean_radiant_temperature, 80
min_vars, 80

ndbi, 81
ndbi(), 32, 82
ndvi, 82
ndvi(), 32, 81

parallel::mclapply(), 67
parse_date_flexible, 82
peak_month, 83
plotBars, 84
plot_ccf, 85
plot_dual_axis, 85
plot_heatmap, 86
plot_map, 87
plot_scatter, 88
plot_series, 89
populate_sample_cache
 (PopulateSampleCache), 90
PopulateSampleCache, 90
print_timing_summary, 90
process_imd_files, 91
process_netcdf_to_dataframe, 92

rate_vars, 92
read_cdsapirc, 93
read_imd_rainfall, 93
read_imd_temperature, 94
regrid, 95
relative_humidity_from_dewpoint, 96
relative_humidity_from_dewpoint(), 21

search_variable (SearchVariable), 96
SearchVariable, 96
seasonal_cycle, 97
seasonal_stat, 98
setup_cds_credentials
 (SetupCdsCredentials), 99
SetupCdsCredentials, 99
show_cache_info (ShowCacheInfo), 99
ShowCacheInfo, 99
spatial_mean, 100
stats::ccf(), 17
stats::lowess(), 89
stats::quantile(), 59
sum_vars, 101

time_operation, 101

utci, 102
utci_category, 102
utci_sparse, 103
utils::sessionInfo(), 51

validate_bbox, 104
validate_coordinates, 104
validate_era5_variables, 105
vapor_pressure_from_dewpoint, 105
varunayan-aliases, 106
visualize_grid_overlap, 107

warm_nights, 109
warm_nights(), 31
wbgt, 110
wbgt(), 113
wbgt_from_dewpoint, 111
wbgt_liljegren, 111
wbgt_liljegren(), 31, 110, 114
wbgt_risk_category, 113
wbgt_shade, 114
wbgt_simple, 114
wbgt_simple(), 31, 110
wet_bulb_from_dewpoint, 115
wet_bulb_temperature, 116