

Package ‘vizintel’

October 31, 2026

Title Visualization Intelligence Toolkit

Version 0.1.1

Description Provides automated data profiling and visualization recommendation tools for exploratory data analysis (EDA). The package inspects a data frame, classifies each variable as numeric, categorical, or datetime, and computes distributional statistics including skewness, excess kurtosis, Shapiro-Wilk normality test p-values (Royston 1995) <[doi:10.2307/2986146](https://doi.org/10.2307/2986146)>, and cardinality. Based on these profiles, the package scores and ranks candidate chart types (histogram, density, boxplot, violin, bar, lollipop, scatter, hexbin, line, heatmap) using an internal taxonomy that accounts for variable types, analysis goal, skewness, cardinality, and data size. Additional functions audit existing ggplot objects for common visualization integrity problems such as truncated axes, lie factors, overplotting, and dual y-axes following principles described in Tufte (1983, ISBN:0961392142) and Wilke (2019) <<https://clauswilke.com/dataviz/>>. The package also checks visualizations for accessibility issues and suggests alternative chart types for a given plot.

License MIT + file LICENSE

Encoding UTF-8

Language en-US

Imports dplyr, e1071, ggplot2, gridExtra, rlang

Suggests colorspace, hexbin, patchwork, testthat (>= 3.0.0)

Config/testthat/edition 3

Config/roxygen2/version 8.1.0

NeedsCompilation no

Author Pooja Thirumal [aut, cre],
Ronesha Navaneethan [aut],
Amrit Pal [ctb] (Supervisor)

Maintainer Pooja Thirumal <poojathirumal70@gmail.com>

Repository CRAN

Date/Publication 2026-10-31 11:30:02 UTC

Contents

plot.viz_recommend_result	2
print.viz_audit_report	3
print.viz_recommend_result	3
summary.viz_audit_report	4
viz_accessibility	4
viz_alternatives	5
viz_audit	6
viz_explore	7
viz_recommend	8
Index	10

plot.viz_recommend_result
<i>Plot recommended charts from a viz_recommend_result</i>

Description

Renders each recommended chart type as a real ggplot using the data stored inside the result object, then arranges all panels into a single view with `gridExtra::grid.arrange()`. Each panel is labelled with the chart type and its fit score.

Usage

```
## S3 method for class 'viz_recommend_result'
plot(x, ...)
```

Arguments

- x A viz_recommend_result object returned by `viz_recommend()`.
- ... Additional arguments passed to `gridExtra::grid.arrange()` (e.g. ncol, nrow).

Details

Call `plot()` directly on the object returned by `viz_recommend()` – the data is stored automatically so you do not need to pass it again.

Value

Invisibly returns NULL. Called for its side-effect of rendering the arranged plot grid.

Examples

```
res <- viz_recommend(mtcars["mpg"])
plot(res)

# Paired mode -- scatter / hexbin arranged together
res2 <- viz_recommend(mtcars, x = "wt", y = "mpg")
plot(res2)
```

```
print.viz_audit_report
```

Print a viz_audit_report

Description

Prints each detected issue with its severity prefix and technical message, followed by a plain-English explanation (the explanation field) on the next line prefixed with "In plain terms: ".

Usage

```
## S3 method for class 'viz_audit_report'
print(x, ...)
```

Arguments

x	A viz_audit_report object returned by viz_audit().
...	Ignored.

Value

x, invisibly.

```
print.viz_recommend_result
```

Print a viz_recommend_result

Description

Print a viz_recommend_result

Usage

```
## S3 method for class 'viz_recommend_result'
print(x, ...)
```

Arguments

x	A viz_recommend_result object returned by viz_recommend().
...	Ignored.

Value

x, invisibly.

summary.viz_audit_report	
	<i>Summarise a viz_audit_report</i>

Description

Summarise a viz_audit_report

Usage

```
## S3 method for class 'viz_audit_report'
summary(object, ...)
```

Arguments

object	A viz_audit_report object returned by viz_audit().
...	Ignored.

Value

object, invisibly.

viz_accessibility	<i>Check visualization accessibility</i>
-------------------	--

Description

Checks an existing ggplot for common visualization accessibility and readability issues, including excessive colours, colour-only encoding, excessive shapes, small text, excessive text labels, and overplotting.

Usage

```
viz_accessibility(plot)
```

Arguments

plot	A ggplot object to check for common accessibility issues.
------	---

Value

A list containing a summary and an issues element. Each issue contains a severity level, check name, and descriptive message.

Examples

```
library(ggplot2)

p <- ggplot(mtcars, aes(x = wt, y = mpg, colour = factor(cyl))) +
  geom_point()

viz_accessibility(p)
```

viz_alternatives	<i>Suggest alternative visualizations</i>
------------------	---

Description

Suggests and generates alternative visualization types for an existing ggplot object. The generated alternatives are displayed via the active graphics device and are also returned for further use. Informational messages about the alternatives can be suppressed with `suppressMessages()`.

Usage

```
viz_alternatives(plot)
```

Arguments

`plot` A ggplot object.

Value

A list containing:

`recommendations` Character vector of suggested alternative visualization names.

`plots` A named list of generated ggplot objects for the alternatives.

Examples

```
library(ggplot2)

p <- ggplot(mtcars, aes(wt, mpg)) +
  geom_point()

result <- suppressMessages(viz_alternatives(p))
result$recommendations
```

viz_audit	Audit a ggplot object for common visualization integrity problems
-----------	---

Description

Inspects a ggplot object by rendering it internally via `ggplot2::ggplot_build()` and running four integrity checks drawn from data-visualization best practices (Tufte, Cairo, Wilke). Returns a structured S3 report with one entry per detected issue.

Usage

```
viz_audit(plot)
```

Arguments

plot A ggplot object to audit.

Details

Checks performed:

ID	Check	Triggers	S
truncated_axis	Y-axis does not include 0 on a bar/column plot	Bar/col geom + displayed y-min > min(0, data min)	"
lie_factor	Displayed axis range distorts data range	Range ratio outside [0.95, 1.05]	"
overplotting	Many points overlap in a scatter plot	Point/jitter geom + collision fraction > 0.30	"
dual_y_axis	A secondary y-axis is defined	sec.axis present on y scale	"

Lie factor note:

The lie factor is computed in **data space** (displayed axis range vs actual data range), not pixel space. Pixel-based computation requires a live graphics device and is not reproducible in a non-interactive context.

Plain-English explanations:

Every issue includes an explanation field with a plain-English description of what the problem means for how misleading the chart looks. This is printed after the technical message when you call `print()` on the report.

Value

An S3 object of class `"viz_audit_report"`, which is a list with:

- `n_issues` Total number of issues detected (integer).
- `n_critical` Number of critical issues (integer).
- `n_warning` Number of warning-level issues (integer).
- `n_info` Number of info-level issues (integer).
- `issues` A list of issue lists, each with fields `check`, `severity`, `message`, `details`, and `explanation`.
- `plot_geoms` Character vector of geom class names in the plot.

Examples

```
library(ggplot2)

# A bar chart with a truncated y-axis -- should flag "truncated_axis"
bad <- ggplot(data.frame(x = c("A", "B"), y = c(50, 80)), aes(x, y)) +
  geom_col() +
  coord_cartesian(ylim = c(40, 85))
report <- viz_audit(bad)
print(report)

# A clean scatter plot -- should return no critical issues
good <- ggplot(mtcars, aes(wt, mpg)) + geom_point()
viz_audit(good)
```

viz_explore

Explore Relationships Between Numeric Variables

Description

Explores relationships between numeric variables using correlation analysis and a heatmap.

Usage

```
viz_explore(data)
```

Arguments

data A data frame or tibble containing the variables to explore.

Value

A list containing:

- correlation: A correlation matrix.
- plot: A ggplot2 correlation heatmap.

Examples

```
result <- viz_explore(mtcars)
result$correlation

result$plot
```

viz_recommend

*Recommend chart types for a data frame's columns***Description**

Calls `profile_data()` internally to understand each column, then scores candidate chart types from an internal taxonomy against the column profile and any goal or variable hint the user provides. Returns a ranked list of recommendations, highest scoring first.

Usage

```
viz_recommend(df, goal = NULL, x = NULL, y = NULL)
```

Arguments

df	A data.frame or tibble with at least one column.
goal	One of "distribution", "compare", "trend", "relationship", "composition", or NULL (default). When NULL, the best-fitting goal is inferred from the column types.
x	Name of the column to use as the x variable (character). When supplied together with y, a paired recommendation is returned for that specific combination instead of per-column recommendations.
y	Name of the column to use as the y variable (character). See x.

Details**How scoring works:**

An internal taxonomy table lists chart types alongside the conditions under which each chart is a good fit (variable types, goal, skewness, cardinality, data size). Each applicable chart starts with a base score and is adjusted:

- +0.15 if the goal matches exactly rather than being a generic match
- -0.20 if the data is skewed ($|\text{skewness}| > 1$) and the chart does not handle skew well
- -0.20 if the column has more than 15 unique categories and the chart becomes unreadable at that cardinality
- -0.15 if there are more than 1000 rows and the chart does not scale well

Charts with a final score below 0.10 are dropped. The top 3 per variable/pair are returned.

Taxonomy overview:

Chart	Best for
histogram	Single numeric, distribution
log_histogram	Skewed numeric (suggests log scale)
density	Single numeric, smooth distribution shape
boxplot	Numeric + categorical group comparison
violin	Same as boxplot, better for larger samples

bar	Categorical counts or low-cardinality cat vs numeric
lollipop	High-cardinality categorical (bar gets overcrowded)
scatter	Numeric vs numeric, relationship
hexbin	Numeric vs numeric with many points (overplotting risk)
line	Datetime vs numeric, trend over time
heatmap	Two categoricals or categorical vs datetime

Value

A list of class "viz_recommend_result". Each element is a list of class "viz_recommendation" with fields:

variable Column name, or "x vs y" string for pairs.

chart Chart type string.

fit_score Numeric in [0, 1]. Higher is better.

rationale One sentence explaining why this chart fits.

goal The goal used when scoring this recommendation.

The result also has attributes `df`, `x`, and `y` (the data and variable names stored so that `plot()` can be called on the result directly, without passing data again).

Side effect: when called in an interactive session, the recommended charts are automatically rendered in the Plots pane via `plot.viz_recommend_result()`. You can also call `plot()` manually on the returned object at any time.

Examples

```
# Per-column recommendations for the whole data frame
viz_recommend(mtcars)
```

```
# Two specific columns as a pair
viz_recommend(mtcars, x = "wt", y = "mpg")
```

```
# Force a goal
viz_recommend(mtcars["mpg"], goal = "distribution")
```

Index

`ggplot2::ggplot_build()`, [6](#)
`gridExtra::grid.arrange()`, [2](#)

`plot.viz_recommend_result`, [2](#)
`print.viz_audit_report`, [3](#)
`print.viz_recommend_result`, [3](#)

`summary.viz_audit_report`, [4](#)

`viz_accessibility`, [4](#)
`viz_alternatives`, [5](#)
`viz_audit`, [6](#)
`viz_explore`, [7](#)
`viz_recommend`, [8](#)
`viz_recommend()`, [2](#)